X 4-5-78 Set CIM #730706 (1)

1/4 Corner west 1/4 7 Haver. 107-13
east 1/4 12 Casc. 107-14.

10-1877 Hunter P 322 no 316 L7 J Donnel & others.
found stake at corner of fence, checked by NWBT.
-16 south found old stake No. 89, set new stake M&L 19.92. (1314.72'

1-1900 R Fraser P 646 No 582 L1-2-11-12. 15 parties
found stake P 322 set new stake
- Meas North 39.88½. (2632.41'
-16 West stake M&L 19.97. (1318.02'

---

same corner used P 645 No 581 same meas N & W.

fence corner now used as corner for surveys.
39.88½.
– Meas North 2632.41? to section corner

4-5-78 Dug 3'x3' on the So. side of the corner post of fence
North and East at the location of a 5/8" rod in place.
Found the mark of an old post (with wood pieces) on
the So. side of the rod. Removed the rod and set
a CIM over a ¾"x 30" rod at its location on the
corner. Corner appx 33' E of center of N-S road.
R.P.'s MHO Disc in W. side of c.p. N 1.24
MHO Disc in S. side of brace post ENE 5.02
Lot corner pin (RLS 6405) W 65.90
S.E corner of house (brick Facing) NW 145.33

Plats measure N = 2624.87 A.S.A measure N = 2625.5 prior to 1963
1963 Survey – Arnold Rost – Fd 1½" sq. pipe at E¼ 12, 2" iron shaft NE½

1/4 Corner West 1/4 7 Haverhill 107-13 (2)
East 1/4 12 Cascade 107-14
#730706

Gov't Notes

7.50 Leave prairie & table land level, a scend bluFF and
Enter Scattering Timber bears Nkl.
28.00 Burr oak 14" in diameter
40.00 Set 1/4 Post - (Burr oak 14" S65°E 55lks.
Burr oak 13" N25°W 170lks.)

Feb. 1858 T. Hunter Pg. 49 No. 72 used 1/4 Cor.
1/16 East 18.28 chs. Then 20 chs. to Cen Sec 7