X 5-16-1974 Co Surv set a C.I.M. over a stone
½" x 24" rod over a cast pin pipe
#733305 (1)

section corner south 32-33 Haverhill 107-13
north 4-5 Mason 106-13

4-1878 Hunter P333 No 327 & 4 N Breckenridge.
found remains of old stake in center road in
line fence north and 2 rods from corner post.
Corner undisputed set stone 4" x $\frac{3}{8}$ x 16. in to place.
-16 east set stake M & L 20.18. (133688'
- meas south. 39.44 | Meas. East 39.49 or 39.56 | T.4 1878

8. 1884 Hunter P391 No 382 & 33 Williams, Hickey
found stone center road set P333. 390 @ 38.4 162.3
- east 25.95 to west edge R R R.W. 17.2.7 R R &
then 11.95 from east " " east to S 1/4 33. 768.7

– Meas north to south right of way rail road R.W.
20.25 1336.5

6-1899 H Fraser P 658 No 586 S 32 State of Minn.
found stone in center road
– Meas west 90.0' (2640.66 to stone 2x8x26 set by old ditch found.)
40.0'

11-1950 Co Hwy Dept. 1968 Road regraded & resurfaced.
1" x 4' steel bar. No Good
spike tele pole SW 46.0'
" power " # 19087 NW 36.0' NE side
cross south end galv culv E SE 36.0 31.0
" north " " " E NE 37.0
1935 B75 P 8 Meas ack 2662.8 Then 2605.0 to S 33-34.
1963 B277. Co HD corner still in place.
P.I. 627.' west of corner

Card # 2. S 32-33 Haverhill N 4-5 Marion (2)

#733305

J Kerr. 6-1947. B 33 P 33 for Jointer.
Corner S W 33 1" drill steel Sp FP S E 46.5
Sp TP S 25.8

J Kerr 11-1951 B 50 Meas to ℄ RR from S 1/4 33 878.9 Spike
37° 57' ℄ J Kerr. 38° 14' C & H D 38° Hunter
10-15-72 Meas east to S 1/4 33 ~~2663.49~~ elec then ~~2663.14~~
Co Hwy Dept 2662.8 then 2665.0
Hunter 1878 2663.76 1878 T H 39.49 or 39.56 ~~No recorded meas east of S 1/4 33.~~

Later found C 1/4 33 - meas East to accepted Corner 2609.31 elec.
meas west to County Hwy Dept iron 2657.32 E.T.C.

Oct. 1857 John Fellows Pg. 41 No 63 shows Sec. Cor.
1/16 west 19.67 chs, 1/16 East 19.90 chs. 1/16 North 19.71 chs.
1/16 South 19.56 (See Survey For S.W 1/4 Sec 33, 107-13 & N.E 1/4 Sec 5, 106-13

5-16-1974 Dug with backhoe for the 3rd time & found a shattered limestone 6½' to 7' deep. Set a piece of calf pen as a riser to the stone, ½" x 24" rod, & the C.I.M. over All. corner lies 3' West & 1' North of the pin that was in place. Removed the old pin.

R.P.s

Top lug E end 24" C.M.P.	5' W. of S.		21.98'
Punch cross in S. end 36" C.M.P.	SE.		33.07'
C.H.D disc N.E. side	P.P.# 19087	N	34.81

1937 - C.H.D. found iron spike in center of small limestones

7-1979 Shot corner in control survey (1979 Remon BK P.103)

5/9/1875 Thomas Hunter (BK 9, PG 111A, 111B) used corner measured north 20.25 chs to RR tracks and 27.20 chs east to center of RR tracks

Section corner Sec 4 32-33 Mark 11 107-13 ③

North 4-5 marsh 106-13

#733305

Corr Nos

84.0- 2" pipe & iron -bound stake 1.

Ontions 4-5-32-33 St. 11 mound. Pipe

SE Ores- Orange, NE Mark woods

5-23-89 C.I.M. down in new blacktop on old Co. Rd. 9

1935 CHD (book 75 page 8) found old spike over small flat limestone 1"x6"x6"