11-18-77 Set CIM #740604 (1)

¼ Corner 6-7 Cascade 107-14.

5-1876 Hunter P295 No 290 & 7 5 parties.
found remains of old corner fence post stub in center
road in line fences N and S which Hunter saw stake
in mound beside post before road opened. Mr Schmelzer
owns his fence north on line and corner post. 2 rods from post.
- set stone 3X4X20 in place of old post with remains
of old post on east side of stone.
-16 east set temp point midway only. 19.96½ (1318.7'
-16 west set temp point prop. Meas short 50 links.
19.74 (1302.84' shes 18.11 (1195.3 for W corner see 7.
-16 south set stone 3X3½X20 M&L. 20.09 ¾ (1326.49'
(over)

-16 Center NW 1/4 S7 set stone 3x5x22 inters lines.
-16 center NE 1/4 S7 " " unmear " "

6-1874 Hunter P 229 no 232. S 6. N Colby.
Corner in road - no digging equipment accepted
fences. north and south S Road running away from corner
- did not need corner only for line of N-S 1/4 line.

present day - terrain favorable - 200' slight slope west
& East in road. road top level to some higher than fields

11-11-71 Co surv. Meas east from nail set as W/6-7
Cascade E 1-12 Kalmar. 3' east of center cross roads.
- set nail at 2498.1 (record) in fair line of fences N&S.
- reset nail due west still on center road and meas south
at 2826.44 (record). 1.2' on line over stones at Center 7
Lee cont H 2

Corel #2. 1/4 6-7. Cascade 107-14 (2)
and stone between Center 7 and 1/4 6-7. #740604
Meas west To nail now 2496.9.
RPT reset nail
35.09. S To 16 D in Top of new corner post of good fence south.
81.54 SW To 16 D in Top first wood post in fence line running
west on south side of road. Corner close To nail &
still in place. grade Dep. and on road slope, doubtful.
Corel least at nail location.

6-1-72 found nail, dug entire area To clay near 6' deep
found nothing - filled Lole reset corner with 1/2" x 3' rod.
and set 18.35' offset west in south road fence for
check from 1 mile S.

11-16-77 Set a RR spike as the corner in blacktop on the line from 5¼7 over the 1/16th N. of the Center 7 and at double the measure from the Center 7 over the 1/16th N. Corner 2' So & and in line with fences N and S. Corner 1.1 So of rod (removed) set in 1972.
RP's: CSD in corner post N 38.01
CSD in corner post S. 33.99.
11-18-77 Replaced RR spike with CIM over ½" x 13" rod.
Govt Mons not found. Found 18" ½ 0.00 Set temp ½ section post East on true line between Sects. 6 & 7 38.35 Set ½ steel post in mound, with tack & ½ chiseled slope. & Orange Orange tapes N. E & S. W.

/740604

7-22-99 MWJ RF AE

1/4 Cor 6-7 107-14 Cascade
fd MAG Nail & Surface of
blacktop 65th St. NW. found
P.K. nail 2 1/2" deep in another
layer of Blck top. found
CIM in good Condition 6" deep
The position of MAG Nail and
P.K. Varied a bit we set
60d spike @ Surface @ CIM
location The Corner falls
2' South of ℄ 65th St. ℄
in line of fence South and
2' East of Main line of
fence running North.