9-7-1965 set C/Monu 1/2" x 24" rod. see details (1)
11/3/09 SET SHORTY CIM OVER CIM #740804
1/4 corner 8-17 Cascade 107-14
1857 Horton P84 no 129 W1/2 L8.
corner used- set 1/16 west M&L 19.86 (1310.76'

6-1892 J Fraser P489 no 464 L17-20-21 Town Board F Yomann, Thos Crawford
found large stake in center road, set stone
-east found stake in road ac NW cor 75 acre plot.
East 21.17 1/2 (1397.55' then 18.68 1/2 (1233.2'

5-1956 J Kerr B63 P12 L line L8 Rossi
ran south line L8 525907 set 1/16 corner on line
1314.93 from LE cor 8 or 1/4 distance (Note: RB. Wrong Method To set 1/16) (OVER)

RP 1/16 sp TP S W 101.4 - sp PP S E 48.4 corner
fairly in line true row north.
1941 B25 P37 found stone with tube in top Cass road survey.
9-1965 J Kerr searched for corner recorded set or
found by Kalb Co Hwy surveyor.
- found stone and tube 3.5' deep 1.56' south direct line.
- run & remeas line. 2628.0 to S W cor 8 (Same B25P37.
1317.35 east to 1/16 pope. 1315.35 from 1/16 to S E cor 8.
- left chainage as is moved C/M to be on direct line.
- set C/M ores 1/2" x 24" rod. lies just north & traveled road.
- nail in power pole #36400 N.W. 80.4
- o in south end 48" galv culv W. 232.0
1969. help McGhie city park survey. meas South to
center 17 as set 2619.2' then 2640.9 to S 1/4 17.

#740804 (2)

1/4 Corner 8-17 Cascade 107-14

1935 - Co. Highway Dept. Book 75, Page - 36
Found stone set on North side of old rotten stake about 2' below surface of road. (Carried point to surface) with 1"x2"x18" stake.
Ties: P.P. N.W. - 42.2
T.P. S.W. - 33.3
measure east - 2631.9
Govt Mon - M. Kanuck 1857
40.00 set temp 1/4 sect. post
West on true line between sects 8 + 17 V 9°3E
40.00 set 1/4 section post - mound with trench, pits, charcoal stake & Orange Orange scribe NE & S.W.

(1857) John Fellows (over

July, 1857 John B. Fellows Pg. 26 No 41 use 1/4 Cor.
Meas. West 39.78 chs.
1/16 East 19.98 chs. M&L to sec. Cor.
1/16 North 19.98 chs. M&L to Cen. Sec,

July, 1857 John B. Fellows Pg. 27 No 43 used 1/4 Cor.
1/16 west 19.89 chs. M&L
Prop line East 24.98 chs., then 14.98 chs. to sec. Cor.
Meas. South 39.54 chs. to Cen Sec,
11/3/89 OLD CIM DEEP IN TWP RD. MUSH & WATER IN HOLE THAT Mc & B CREW HAD DUG UP THIS MORNING. SET SHORTY C.I.M. 1" BELOW SURFACE
RP's
SE COR. HEAD WALL ON WEST END LARGE CULVERT
NW 69.85
SW COR. HEAD WALL ON EAST END LARGE CULVERT
NNE 35.15

#740804 (3)

1/4 CORNER 8-17 CASCADE 107-14

7-18-97 - FOUND CIM IN GOOD CONDITION DOWN 4" IN BLACKTOP 55TH ST NW. TIE OUT OF CORNER FOR 55TH ST CONSTRUCTION. FOUND CITY CONTROL PT (1/2" REBOD) TO USE AS REF. IN BLVD OF HOUSE #5505 44TH AVE NW.

℄ 44TH AVE NW E 24 1/2', ℄ RES. DRIVEWAY N 41 1/2'.

T@ CITY △ 7RT RED LIGHT ON WATER TOWER FOR NORTH PARK TO 1/4 COR 145° 27' 50" HOR 103.16

11-12-97 - LAID OUT CORNER FROM CITY △. SET PK NAIL IN NEW BLACKTOP 55TH ST. 1' N OF CRACK IN ℄ 55TH ST + 5 1/2' E OF B.C. EAST CURB 44TH AVE NW.

(740804) F

✓ 1/4 COR 8-17 107-14 CASCADE 12-14-98 EPA JJ BB

SET 1" SR PIPE/CAP AS FINAL CORNER

1' NORTH OF CRACK IN ℄ 55TH ST NW

25 1/2' EAST OF ℄ OF 44TH AVE NW

5 1/2' EAST OF B.C. EAST CURB 44TH AVE NW