8-9-1966 set C/M over orig stone found with ½"x3' rod (10/7/86 reset C/L.M. over stone as it was knocked out ①

#7410006

1/4 9-10 Cascade 107-14.

4-1870 R. Perry P 108 no 147 S 9 & 10 M.C. Clark.
set a stone as 1/4 Cor. not stated as on line but
mean of N line 20.10 1/4 line 20.06 and S line 20.01½.
Makes it set N&L 39.40 2600.4
-16 N set stone N&L 19.70 (1300.2
-16 S set stone N&L 19.70 (1300.2
-16 E put post made mound and pits. N&L 20.06 (1323.96
to point found as center sec. 10 but not retained.
-16 W put a stake N&L 19.94 1316.04 to center 9a
stone set. (no desc. now in bottom deep road ditch (corner questioned)

6-1874. Hunter P256 No 256 Sec. 10 Phile Boardman searched for stone set P108, used. corner of fence running east and corner for line only east. to set Center. post Assumed as having been set and stone removed.

5-1911 Chas Larson. P166B. Secs 9 and 10 J Clason Pennington.

"8" found limestone.

Meas west. 39.88 2632.08

11-1916. J Kell P252B. Bardel. and others S 3-10. Survey states "Started on the E 1/4 9 and ran a random line north 1 1/2 miles. final meas 7759. - finally set NW 10 at 2600 making North 1 mile. 5159. (Mr Sutfgen survey B78 P44. S 3 line meas very carefully north from see corner set 5154.0 on this exact line direct to N 3-4.

Card # 2. 1/4 9-10 Cascade 107-14. (2)
ran line S of 1/4 9-10 (undescribed) P 253. #741006
"found 1/16 corner at 1297. (corner not described)
reset stone at SE 9 at 2600 or 1303 from 1/16 corner.
No description of events leading to "reset" of this corner.
or of corner itself (see 9-20-15-16., 6-1935 survey)
- Page 257. ran & meas from 1/4 10-11 west to 1/4 9-10
5284.5' - set Center 10 Midway 26 #2.25 also
set Center 10 Midway 2609.5 on N-S 1/4 line.
found for Center 10 Dudley survey. B93 P13 NE 1/4 10. 11-1966
Meas east. 2632.14 North 2615.3 result of true inter lines.
See B10 P8 for data on N-S line betw sec 9-10 believed
1916 survey data, doubt if line run this survey. 6-1935.

8-1966 found huge. 6 x 24 x 30 stone believed set by J Kerr 1916 as: NW Cor 10, set C/M in its place and meas south found 1/16 fence running west at 1297.0 and stone at 1/4 9-10 at 2595.2. where C/M set 8-9-66. R 1300 & 2600. found perfect limestone (no size noted). in perfect line fence east and very little west of fence south. drove 1/2" x 3' rod on SE side of stone with C/M over center stone. - set long model T Ford steering column shaft under fence east driven near ground level. E. 50.0' red cloth on fence. -
Corner used in Qualey Zappers Hill survey to set Center. B93 P13 10 at True miles lines (not 1916 method.)

12-28-72. See (3) card 9-10-15-16. for line south finding a limestone believed to be Perrys 1/16 stone at 1299.9. R1300.3 (Must investigate carefully line & meas north later.

Card # 3 1/4 9-10 Cascade 107-14. #741006 (3)

3-22-73 cont. line north carefully set up in 12-28-72. on 125' (S) west at 1/4 9-10 and 1/16 stone S.

P.O.T. 125' W at 1/4 9-10 is 1.7' N of CIM

125' W at 1/16 S is .82' S of stone.

did not remeasure line at this time.

line fell almost exactly 135.0 west of long 16" boulder roughly 5" x 8" ± on west side of corner post of fences west and north. which in 1966 was 1297 from N.

- I dug and found vertical (nearly, leaned east on top some) limestone 3" x 8" x 16" in clear soils almost exactly 10' west and 2.3' north of J Kerr stone making meas North 12.94.7 and south 1300.5 (1966 meas) also found

boulder with cross at NE corner 1 acre triangle set up by J Kerr for J. Bandel in 1916. which is likely on line of existing stones.
- 1/4 9-10 C/M and limestone set by Perry as 1/16 corners N and S now line up and mean within reason. 1300.5 No 1299.9 So
- Cent aerial north and set nail on 125' east and 5.8 north of C/M. or 1300.5. (See 34-9-10 for R.P.S.

1/4 9-10 now final and positive.
original 3-4-9-10 whether stake by Perry or Stone by Larson now definately gone. dug To clay in cult field. must reset. from line run in from South and east 3-22-73.
Gov't Notes on Hancock 165'/ 40.00 set 1/4 station post in mound of brush pits, chained stake & Orange Orange stakes W. E. & S. ea.

1/4 COR 9-10 CASCADE #741006 (4)

10/7/86 FD CIM ON TOP OF GROUND AT FENCE CORNER OF FENCE E & S DUG DOWN TO STONE WITH 1/2" RE-ROD ON S.E. SIDE STONE DOWN 2'. RESET CIM OVER STONE & CHECKED AT 50.0 FROM KERR SHAFT UNDER FENCE EAST. SET SURVEY MARKER SIGN & POST .7' NORTH. CORNER IN LINE WITH FENCE EAST & 2' WEST OF FENCE SOUTH CORNER POST NOW GONE.

11/20/89 FD CIM IN GOOD COND. NOW ON BACK LOT LINE OF NEW HOUSES. RESET SIGN & POST 0.8' NORTH