/ 4-17-75 Set C.I.M. over ½" rod. #742004

¼ Corner 20-29 Cascade 107-14

4-1858 Hunter P52 no 75 N½ S29

used corner - set 16 east M&L 19.50 (1287'

- meas south 19.56 (1291' also set

- 16 center NE ¼ 29. - meas from this corner N 19.65 (1296.9

west - 19.46 (1284.4'

2-11-74 Ran line from N ¼ Cr. 20 over Center 20. Line fell 2.7' East of 4" steel post set in concrete at intersection of N-S and E-W fences. Meas. N. from this point = 2648.21'

4-16&17-75 Set C.I.M over ½" rod under E-W fence at point established in 1974. Dug large hole at fence intersection but found nothing

Meas. West = 2651.68

Gen'l Notes pr. Kanick 1851

40.00 Set Iron Post, post West on true line between sects 20 & 29

40.00 Set 1/4 sect post in mound V 9°30' with trench, pits & charcoal stake & Osage Orange scribs NE & SW.

July, 1857 T. Hunter Pg. 36 No. 58 Must have used this Corner to set Center Sec. 20 (See Survey for Break Down)

June, 1863 R.C. Compton Pg. 75 No. 109 used 1/4 Corner to Set Center Sec. 20 & Subdivide S.E 1/4 Sec. 20

2-21-84, 1/4 20-29: Shot CIM from control point Osmon