/ 4-17-75 Set C.I.M over 1/2" rod

#742005 (1)

section corner 19-20-29-30 Cascade 10 7-14

10-1877 Hunter P321 no 315 S19 D Norman E. Esper.

Meas line from SW cor 19 east to this corner.

Could not find any evidence or knowledge of corner by careful digging and search. set No corner.

8-1857 Hunter P36 No 58 N 1/2 S30

used corner run & meas N line 30 set 1/16 corners.

from SW 19 east 17.78 - 20.00 - 20.07 - 20.07

orig Govt notes 17.50 - 20 - 20 - 20

5-18-1863 Compton P.70 No.100 used comm

Apr. 1858 T. Hunter P 52 No. 75. Shows 5 sec Cor. Meas. South 39.70 chs to 1/4 Post (See Survey N 1/2 Sec 29).

Jan. 1974 Co. Surv.

Set ½ Temp. P.K. nail in ℄ N-S Road ℄ Acreage of fences ± 5' W
Used this point for Measuring purposes only

Co. Surv. Disc. in Gate Post — NE - 34.05
Co. Surv. Disc. in P.P. — SE - 28.72
Co. Surv. Disc. in Gate Post — N.W. 35.47

4-17-75 Reset this corner by lost method (double proportionate measure) Meas E. = 2651.68' Meas. W. = 2651.68'
Mean N = 2633.51' Mean S. = 2633.51'
Set C.I.M. over ½" rod in east edge of N-S. road and ± 10' S. of fences E and W
R.P.'s C.S.D. in Gate Post NW 50.20'
C.S.D. in Gate Post NE 34.85'
C.S.D. in Power Pole #21857 ESE 14.02'

Cascade section corner 19-20-29-30 (2.
Set 4"x4" post 1.5' in ground #742005
50.00 set post to corner to set
19-20-29-30 encased around
with 4-rock piles, chained
stake at Osage orange stubs
at each angle

2-14-84 Sec Cor 19-20-29-30: Found CIM (down 1.0) at
East edge blacktop mat on N-S road (dim 1½')