7-12-77 set ½"x 3" pipe in conc paving as final corner (No New M/P's) #742004 (1)

¼ Corner 19-20 Cascade 10-7-14
D Norman
C Eager.

10-1877 Hunter P321 No 315 & 19
found stone in center road, a boulder,
set by W. Crawford where orig stake stood.

6-1892 Thos Fraser P489 no 464 & 17-20 F Joman
T Crawford.
Iron board.
found large boulder which Thos Crawford
avers he helped set from orig corner.

Co Hwy Dept has ⅝" steel rod in place as corner pipe below.
1968 Mease line from SW cor 17 as set C/M south
To rod in blacktop 2627.85 ⅙ fence east 1327+ from north.

over)

RP 1/4 19-20. ~~Sp in power pole.~~ ~~N.E. 42.85~~

~~Possible Sp in " "~~ ~~So. No. 49.7~~

~~Center bell top of tele terminal~~ ~~N.W.?~~ ~~45.9~~ S.W.

~~1969 Mag Shiv mease from rod west To rod drove~~

~~on Beach top set by line & mine from corner post~~

~~at Delta over stone found at 1/4 south 2648.9 +/-~~

1941 Co ND B11988. found stone and stake.

1" pipe 4' long (set 5/8" rod 1957 -) 1941. 0 big Δ 2° 5' N from W, Lt gong E mead west 5141.5

Co ND 1966 B313 5/8" rod.

Sp m PP NE 52.14 ok ~~Sp on TP NW 76.44~~

Sp D m TP SW 49.02 ok Sp D on top cor FP SE ~~48.6~~ Post pulled sely 2646.63

Measured 5142.32 east To accum cor. Center 20

Δ 2° 6' lt from west.

Jan. 22, 1974 found 5/8" rod - in road 2' So. of ft (checked above Ties

1/4 Corner 19-20 Cascade 107-14 (2)

#742006

Co. Surveyor Jun. 4, 1974

dug with Tractor 11' deep and did not get Thru road fill, gave up and accepted 1" pipe 4' long with 5/8" rod riser as official Corner. Removed Pipe & rod while digging and did not replace as new Road grade To be raised about 5' To finish grade.

Co. Hwy. Dept. set Transit Ties 100' N. & S. - 1/2" rods other Ties will get destroyed.

1/4 line run from W.1/4 Cor. 19 (a CIM) To this 1/4 Cor. falls 0.5' N. of Cen. Sec. 19 (boulder found 9' deep.)

over.

1/4 line run from E. 1/4 Cor 20 To this 1/4 Cor. fell very near old stake at Cor. 20 which we accepted.

4-16-75 Found 1974 tie destroyed or buried deep. Remeasured 1 mile E&W of this corner as in 1974. Used the line projected from E over Center 20, and at our former measure. Set a 3/4" x 10" rod as the corner.

R.P.'s C.S. Disc on S.W. side power pole # 42799 SE 67.35'
C.S. Disc on N.W. side power pole # 21848 NE 77.25'
Corner fall 5.95' South of E-W ℄ and in center of road N & S

11-17-1975 dug up Co Hwy Dept. - Transit Tie rods 100' N. & S. N. rod was 10' deep & So. rod 14' deep. - Checked These rods To our 1/4 Cor So. 1/2 rod was 99.91' & N rod 100.22 - Line fell on E. edge 3/4 rod - left as found

Cascade 1/4 corner 19-70 #7420061 3

Gen'l Notes on Karnick 1859

40.00 Set post in mound w/6 trench, pits, charcoal stake Osage Orange seeds NE+S.W

June, 1863 P.C. Compton Pg. 75 No. 109 used 1/4 Corner to Set Center Sec. 20 at intersecting lines