#742104 (1)

¼ Corner 21-28 Cascade 107-14

No records - Compton P.74 (used ¼ post)

½" rod set midway on S line section 21.

6-1960 J Kerr B 81 P 32 #21 Prec. Intaacments

run south line section 21 found rod to be.

Midway and 8.45' north of straight line

491.9 north center Co road ¼ as in place 1960

- 16 west set steering shaft M+L 1316.1

RPs ¼ corner spud in fence corner east 50.3

over.

spud in power pole. SE 114.3

-16 north. origin unknown. M&L 1324.5 (possibly McGinn
RPs above 1/16. Sp PP NE 58.78 - Stat F.P. E 50.00
Sp PP SE 91.32 - " " W 50.0

-16 center SW 1/4 S21 B81P32.
Measured 1314.4 north 1319.25 or 2634.5
Sp PP SE 30.5 Sp PP N4W 31.0

June, 1863 P.C. Compton Pg. 74 No. 108 Shows 1/4 Cor.
used to set Center Sec 21 at Intersecting lines.
1/16 North 15" White Pointed Top stone

Nov. 1863 P.C. Compton Pg. 78 No 117 shows 1/4 Corner
used to Set Center 28 at intersecting lines.
Set 1/16 west M&L to Sec Cor. 20-21-28-29

¼ Corner 21-28 Cascade 107-14 (2)
#742104

Co. H.D. 1940 B. 119 - p. 56
Set red head as S. ¼ Cor. Sec 21 by M. & L.
2631.95 East & West
p. 55 - S. ¼ Cor. 21 397.2' ~~N~~ E. of & Co. Rd.

Co. H.D. 1936 B. 89 p. 75
Set square iron spike for Corner. from Ch. N.W. RR. ties
Ties shown as 303' E. of R.R.
486' N. of R.R.
612' diagonal Meas.

McGhie - 1956 - used in I.B.M. Land survey
found 1"x2" hub - replaced with 5/8" rod
Ties: spike in Tel. p. 36.5' SW.
spike in fe post - 38.35 N.W.
Steel fe post - 30.25 - West.

Meas. E. 2633.4
Meas. N. 2649.0 (1324.5 x 2)

Co. H.D. Aug. 1972
reset 3/4" iron rod as 1/4 corner in new Bit. Surface
Ties: nail & disc in Bit Curb — N.W. — 6.76
nail & disc in Bit. Curb — S.W. — 7.11

8-5-75 Center of SW 1/4

Dug with backhoe in ditch on N side of Co Rd 4 at location of 1 3/4" x 40" pipe. Found pipe to be over pointed limestone and would stake 5' deep. Set scrap iron and stone around stone and reset pipe over all

R.P.'s CSD in power pole SE 30.59
CSD in power pole NNE 41.56
W edge 6" sq. iron post up 3 1/2' NE 55.6

Cascade 1/4 corner 21-25 #742104 | 3

40.00 set temp 1/4 steel post

West on true line between secs 21-28

40.00 Set 1/4 section post in mound 5' SW

with bronze plate, charred stake &

Orange Orange rods W. E & S. W

2-22-84, 1/4 Cor 21-28: Found 5/8" re-rod driven in blacktop. Curb to West now gone so couldn't verify C.H.D. tie. Shot rod. (Dwg 8-107-14-6)

10/21/86 1/4 COR. 21-28 NEW B.T. OVER IRON. DUG FD 5/8" R x 2½" ROD LYING FLAT, BUT OVER ANOTHER 5/8" ROD DOWN 2½" WHICH SEEMS FIRM, CAN'T BE SURE WHICH IRON SHOT BEFORE

1/4 COR 21-28 107-14 CASCADE "742104" F
FOUND PK NAIL @ SURFACE OF BLACKTOP CR 151.
2½' W EXTENSION ℄ FROM NORTH. POWER POLES
WITH TIES NOW GONE.