9-12-77 Set ½" x 3" pipe as final cor. in Conc. pavement (1)

9-6-1963 Set C/M over 1¼ x 30" pipe

4-15-1975 Reset CIM over 1¼" pipe (Top of pipe down 2½') orig CI. Taken out during 1974 Grading CR #4

¼ Corner 20-21 Cascade 107-14

#742106

9-1857 Hunter P 36 No 57 N½ of 20

used corner - Meas west 19.66 - 19.66 - 20.04 - 20.04

6-1892 Thos Fraser P 489 no 464 S 17.20 F Yorman J Crawford Jonn Beard.

Run corner in by line from W ¼ 20 over center 20 intersected by line from NE 20 to SE 20.

set rounded stone boulder 10" x 19"

-16 North set stone 5x10x18 19.90 (1313.4'

-16 south irregular 18" L.S. 19.91 ¾. (1314.55

-16 west set stake mark L 2 links from Hunters 1966

5-1960 J Ker B81 P32 S 21 Prec Instr. (over

Run line from NW 21 to SW 21 found stone as record
at 1/16 1314.9 .5 R. 1313.4 each of line corrected. then pointed boulder
at 1314.9 (2629.8' then a stake driven into clay at SW21
set- R 1314.55
1315.6 then 1315.6 to SW 21, other property corners
between. 1/4 corner replaced with CIM with 1½"x3" pipe.

R.R. steel fence post ~~S~~ 9'
appox center black top road. S 185.0
line under fence N-S ~~west~~ no E-W fences.

Co. H.D. 1936 B. 89 P. 75
Set 1" drill rod by Line & meas. From N.W. Cor. 21. over
1/16 Stone South-fd. 1315.3 - 1315.3 (apparently did not find
boulder as found by Kerr 1960

1/4 Corner 20-21 Cascade 107-14 Card #2

#742106

4-15-1975 Dug down with Jack hammer to 1¼" Pipe 2½ deep. Set C.I.M. over pipe in New Road grade Co. Rd. # 4
R.P.'s

CSD ~~Plastic~~ disc P.B.# (21814) S.W. 66.91 ~~66.88~~
Top center of east end Main Culvert S.E. 53.37
~~2"x 2" C.H.D. Hub — N.N.E.~~ ~~88.79~~

Gen'l Motors M. Kanack 1854
40.00 Set ¼ sect post with trench pits
Chiseled Sink & Orange Orange sect-
N.E. & S.W.

over

June, 1863 P.C. Compton Pg. 74 No. 108 1/4 Corner Missing
Established it midway & on Line between two
Nearest section Corners. used to set Stone at
Center Sec 21 at intersecting Right lines
1/16 East set Stone 2 1/4" x 3 1/4" x 19". Stones at
Centers of N.W & S.W 1/4's

June, 1863 P.C. Compton Pg. 75 No. 109 used 1/4 Corner
to set Center 20 at intersecting lines. Subdivided
N.E. 1/4 & S.E 1/4 Sec. 20

7-12-77 SET A 1/2" x 3" PIPE AS THE FINAL CORNER IN THE
CONCRETE PAVEMENT.

6-7-99
HPA JPJ MCMR

"T42106" 1/4 COR 20-21 107-14 71

SET 5/8" COPPER PLUG WITH PUNCH MARK IN IT
AS CORNER. CORNER FALLS 0.1' S OF ℄ CSAH #4
+ 8 1/2' W OF ℄ GENERAL WAREHOUSE COMPANY DRIVEWAY S.
CHD IN PP # 23515 NE 127.34'
CSD IN PP # 21814 SSW 66.72'