7-20-1964 set CIM over stone. #742205
section corner 21-22-27-28 Cascade 107-14.
5-1870 Perry P178 no 189. regular survey-
renewed and used corner

1941 JKarr B24 P78 L22 Sam Allen.
used corner a limestone now.
Meas north 5335.4 set no 1/4 corner north.
1951 B52 P40 L22 Sch Dist 97 Meas 5336.0

7-1964 set CIM to preserve corner
corner lies within 10' large trans power pole.
North west corner Northgate 3 subdivision

1936- C.H.D. Book # 81 page 56 - Stone in Fence Corner
Gov't Mon's M. Kavanagh 1954
80.00 Set post for corner to stand mound with
21-22-27-28 in charred stake, French
pitts + Orange Orange scrods at each
angle

10/21/86 FD CIM DOWN .7' ON NE SIDE LARGE POWER POLE, .15' NE OF NE SIDE OF POLE
R.P.'s CSD IN NW SIDE P.P. SW 1.29
CENTER OF 4' TALL CONCRETE IBM MARKER E 6.15±
FIND CORNER BY GOING TO INTERSECTION 25TH AVE N.W. & 26TH ST NW, THEN GO NORTH BETWEEN HOUSE # 2503 & # 2461 TO BACK OF LOT & CORNER