(1) 8-24-64 set CIM over 1 1/8" x 10" rod. [#74256] June 5-1980 by City Const

6-18-80 1" sq pipe with cap

1/4 corner 25-26 Cascade 107-14

set CIM one place of rod long used as corner. over 1 1/8" x 10" rod

Sp in PP ~~S 29 E~~.

MHD in PP NNE 34.69

Gov't meas ~~N. Fork~~ - 85 /

40.00 set 1/4 cor. post, no mound

with burned pits, charred stake

& Osage Orange scribe N. E. 1.5 ea

4-1979 found CIM

(1850) T.H. → over

May, 1856 Thos. Hunter Pg. 8 No. 13 Shows 1/4 Post.
1/16 South 19.60 chs. M&L - B.T.'s (N 81¼° W 136 lks.) & (S 36¾° E 55 lks.)
1/16 East 20.71 chs. M&L to Center Sec.

6-18-80 This Corner destroyed by city fixing frost boil
Found ½" Iron at N.E Cor. lot 1 & Pipe & Cap at the
S.E. Cor lot 1 of the resub. of out lot 25 Northern Add.
by McCrie & Betts. Set a 1" x 35" Pipe with Cap
on line with these two Corners and 33' North of
½" Iron. Also fd. Cap & Pipe at N.W Cor. lot 1 & checked
Angle (at ½" Iron) to Corner as set & Checked
ok. with Plat
R.R.S. Corner in ℄ 19th st N.E.
M.H.D. Disc E. side P.P. N.N.E. 34.80' M.H.D. Disc W side P.P. S.S.W. 21.99'
Brick S.W Cor. Bldg. N.W. 103.31' Top Center Fire Hydrant S.E. 106.21'

(#742506) (2)

(2) 1/4 Corner 25-26 Cascade 107-14

1980 Kastlers (State Plane System)

N 19° 44' 55" E 34.69 to Disc in pp. (this may be copied distance)

S 74° 42' 05" E 102.78 to cap & nail in power pole

S 40° 59' 05" E 59.23 to corner of Foundation

S 9° 26' 55" W 21.97 to disc in power pole

Sept. 1858 T. Hunter FB. 56 No. 82 shows 1/4 Post
Mkd North 20.32 chs. M&L to Sec Cor.
Meas. East 41.42 chs. to Cen. Sec. 25