X 1972. corner East sewer pipe over stone.
11-3-76 cord
#750106 (1)

1/4 Corner 1-2 Kalmar 107-15.
6-1873 Hunter P232 No 234 & 1 H Bowman, N Grimm
Corner gone but Wm Moore anera cornerstake stood
in middle of 10' road grade and in line fence south.
set stone with burr oak stake on north side at that point
- 1/16 east set stake N&L 19.94. 1316.04

---

6-1930 J Kerr. B 3 P41 & 1.
found stone - ran & meas line south to stone
at 1-2-11-12. set iron at 1/16. S. found. 1972. and
pipe at 1/64 & 1/16. found 1972. (also found McGhee iron NW 6' ± ones)

5-1959 McGhie.
found stone with cross.
Sp fence post brace. NE 19.95
" power pole N 13.6.
" tele pole SW 61.5

No road there unless private drive to farm west.
1972 buried corner, found stone placed Cast iron sewer pipe over stone. Corner in wet area north of road as it curves toward farmstead. Power pole N now Hg complex ~~with insert base~~ and transf controls. Corner safe until serious grading as corner in waterway etc.

11-3-76 Pipe set 1972 gone and R.P.'s also. Found boulder ±15" long coming to a point but leaning North - Dug down beside boulder and found 2½" diameter hole filled

#7501060 #2

¼ Corner 1-2 Kalmar 107-15

(continued) with black dirt which accepted as old stake set on N side of stone as recorded by Hunter.
Set R.R Spike 6" S of hole and CIM over spike.
R.P.'s: N end 30" C.M.P. (Bent down) SSW 5.8
SE Corner 3½' sq metal box on cone. bore NE 12.6
~~SE~~ ~~Corner~~ Spike in W side 20" diameter power pole
& graded rock driveway (E-W) on curve to South going West 5. 18' ± North 14.57 015
CIM .45' N of point taken by Cedric. Cedric's nail SSE 9.40

Gail Watts Ranch 1854

40.00 set temp. ¼ steel post

5 9' E on true line between steel 142

39.98 set quarter steel post

Bur Oak 10 S 50 W 125

Bur Oak 12 N 18 E 137

8/22/96 FD CIM OR CULVERT SOUTH 6' TO BE REPLACED! CORNER MAY BE DESTROYED. RENEWED REFERENCES, SPIKE (DRIVEN FLUSH) IN HUBE POWER POLE N 14.56 "+" CHISELED IN SE EDGE (UP 1.1S FROM CONC.) 3½' SQ METAL BOX NE 12.63

---

D [redacted] 1-31-95 V.FANGMAN TOOK REFERENCES TO COMPUTED POSITION OF CIM. SPIKE (DRIVEN FLUSH) ON W SIDE OF PP NORTH 14.56'

PK ON NE FACE BRACE POST SE 36.49'

PUNCH HOLE ON N END 30" CMP SW 14.54'

CENTER BROKEN OFF STUDDED T POST SSE 0.21'