X 11-14-1975 Set CIM over 3/4"x16" pipe in field
Set by W.E.F. Meas. from East ¼ on Sec. line. No Ties: (1)

¼ corner 3 - 10 Kalmar 10 7-15

12-1893 W Fraser P540 No 501 ∠E¼ 3 NE¼ 10 parts of Elford, Koelsch.

"found post planted as corner"
used corner fence post as corner to
set 1/16 corner east at 19.91½ = 1314.39 M & L 26.28.78
also set a stone 4.97½ = 328.35 north of above 1/16 corner. #750304

---

also
2-1871 Perry. P151 No 175 ∠10 NE¼
found orig corner standing and 2 B trees.
- 1/16 east found old stake.
- south 9.94 chen 2.48½ chen 4.97 chen 2.48½ to ¼ cor.
in line center 10. undescribed

11-17-75 Corner comes in open field. Set C.I.M. over
3/4" x 16" pipe deep at Will Fraser full measure (2628.78)
from 2-3-10-11 and on line from 2-3-10-11 to
line of fence ± 400' W of 1/4 Cor 3-10 running
West to area of 3-4-9-10. Checked line from
N1/4 Sec 3 over fence post near Center 3 which
placed corner 8' W and line from S1/4 Sec 10 over
corner post location near Center of Sec 10 which
placed corner 20' E. Bolt location to extreme
to disagree with W.F. Corner also fits N-S
fence on E side of woodlot surveyed by McDowell
in 1861 28 rds. W of 1/4 Cor 3-10 within 1'.

(measure 2633.063 W to CIM)

Kalmar 1/4 corner 3-10 #750304 1Z
Gov't Notes Karrick 1854
40.00 Set temp 1/4 sect. post
West on true line between Sect. 3 & 10 V 9° 35 1
40.00 Set 1/4 sect post
Ironwood 10 S 41 E 44
Ash 9 W 20 W 59

Jan, 1859 Samuel McDowell Pg. 65 No. 91 Shows 1/4 Post used in breakdown of N.E. 1/4 of N.W. 1/4 Sec. 10

March, 1864 P.C. Compton pg. 79 No. 119. used 1/4 Corner to break down N.W. 1/4 sec. 10. 1/16 west 19.95 Chs. M&L to sec. Cor 1/16 South set M&L (No Meas.)