X 11-14-1975 Set CIM over ½"x18" iron rod – set using fence East as N-S Location & proper note meas. between ¼ Corner E & W

section Corner 3-4-9-10 Kalmar 10-7-15.

#750305

1-1878 Hunter P326 No 320 & 9 & Eastwood, & Keesen.

found orig corner lying on ground, also stub of stake in ground

tested 8 trees standing and stumps.

11"	B oak	N 57 E	51 lks.	gone
18"	"	S 40 E	62 "	gone
12"	"	S 35 W	33 "	gone
18"	"	N 40 W	79 "	gone

– Meas West 40.11 to stake driven well down from BT.

→ Good Note for Hackberry

March, 1864 P.C. Compton Fg. 79 No. 119 used See. Corner for breakdown of N.W ¼ 10 – 1/16 East 19.95 chs. M & L

1-14-75 Dug at least 10'x 10' with backhoe but could not find remains of corner post to fence E or stake as recorded by Hunter. Set CIM over ½"x 18" rod in line of fence E and at proportionate measure between ¼ Cor 4-9 and ¼ Cor 3-10. Set steel fence post (up 2') as guard. Corner at edge of field.

R.P.: Spike and CSO in 12" Twin Oak SSE 54.42
Spike and CSO in 12" Twin Bet Elder E 16.75

Mean S = 2621.19 Mean N = 2632.22

60.00 Govt Witness Corner 1954
80.00 Govt ¾" steel post for corner to steel 3-4-9-10
Hackberry 12 S 35 W 33
" " 18 N 40 W 78
" " " N 57 E 57
" " 18 S 40 E 62