W 1/4 Sec 6 Kalmar 107-15 (T)
8/7/89 CHD SET 5/8" BRASS PLUG #750606

Gov't Notes - Set Quarter Sec Post

Br. Oak 10" So 72° W 165 lks.
Br. Oak 5" N 2° E 337 lks.

Dec 1892 A.A. Crampton Dodge Co. Surveyor
Fd. Corner a Limestone also B.W. Bearing Tree
set Iron at 1/16 South 19.93 M & L
Set Iron at 1/64 south 9.96 1/2 M & L
(→ of the above 1/16th

11/15/78 Dug from a point 1' East of the traverse nail (which is 1' West and 1 1/2' W & 0 East for 3' and South for 7 1/2'. There were no old roads or black soil beneath

the existing road - only fill to clay. It looks as if the area was once a slough and had to be subcut. We were digging on A.A. Crampton's, measure from the stone found @ W6-7 (which would come approx 3' So. of the T.n) and at Cor't measure from the S.W. Bearing tree still standing. Found nothing. Chained 1313.5 to Fence west at the 1/16th So. which was ~~obs~~ set by Crampton. The road here is in a slight cut Dipped over a large area with the C.H.O dip needle. Found nothing.

11/16/78 Dug 3' to 4' North from the N. edge of previous hole. Cut out a 1"x2' hub in the crushed rock beneath the blacktop. Dug to clay. Found nothing further.

#750606 (2)

¼ Corner W¼ Cor 6 Kalmar 107-15

3/25/80 Set a 5/8" x 16" rod from the SW bearing tree standing (but dead) in field. Corner ½' East of ℄ N-S road and just slightly North of the line of the fence West. The corner is .45 N and 3.95 East of the t.n.

RP's:

C.S.D. in South side pp # 23118 SW ~~44.29~~ 44.19 7-85

C.S.D. in North side corner post W 45.70

Spike in North side c.p. SE 50.40

Top Center 6" square tele bol NE 50.95

Corner Notes

40.00 S.E. quarter of sec. - post lost

Br. Oak 10 S. 72° W 105

Br. Oak 5 N 2° E 537

7-11-85, W. 1/4 Cor 6, Kalmar: (Bruce) set 5/8" re-rod 105.13 ESE of the corner and on line to a nail in plastic disc in pp # 23119. Rerod 7½' South of the ℄ of the road East.

Checked old R.P's @

SW 44.19 CSD in S. side pp # 23118

W 45.69 CSD in N side C.P.

10/27/88 SET A P.K. NAIL IN THE ℄ CRACK OF CO. RD. #5 BY THE TIE AND LINE FROM THE R.P. IRON EAST OUR PT. IS THE MEASURE OF 105.13 WESTERLY OF THE R.P. IRON THIS IS .18' WEST & .02 NORTH OF THE C.H.D. DRILL HOLE SET IN THE SUMMER OF 1988

8/7/89 C.H.D. SET 5/8" BRASS PLUG IN ℄ C.R. #5 / C.H.D. DISC. IN C.H.D. DISC. IN STUB POLE NE 57.97 / P.P. W 58.95'

104.23 S 47° W 1.70