9-4-1964 set C/M over 1" rod & stone (1)
8-7-89 C.H.D. SET 5/8" BRASS PLUG #750706
1/4 corner. West 1/4 7. Kalmar 107-15
east Dodge county.
4-1897 H Fraser P 607 No 552 & J Hoffman.
Corner gone. set limestone M&L. 39.74 1/2
2623.17.
-1/16 south. set stake M&L 19.87 1/4.
1311.58.

Co Hwy Dept set pipe over stone. Monumented location

9-1964 J Kerr. found corner. Kalmar Twsp survey.
set C/M over 1" rod & stone in this survey.
-Meas east to E 1/4 7. 5216.05
(over)

Dirc power pole N W 53.9.
West road fence running N & S. W 45.3.
Lies in center black top - no east-west fences

11-1946 J Kerr B 32 P 43. Plat of Sec 7.
S W 7. stake by fence corner and gun barrel.
16 N. stone on plat at 1311.15 when 1311.77 to limestone
with pipe riser as 1/4 corner total 2623.92.
- Cont to N W 7. 5247.85. or 2623.93 proving W Traverse line.

10-1964 J Kerr B 89 P 58 found corner set C I M.
ran & meas line east to stone at 1/4 7-8. 5216.05.
set 1/16 iron final east. 1254.82. and C I M as center 7 at.
1324.4 or 2579.92 leaving 2636.78 from Center to E 1/4 7. Sec Center 7.

#750706 (2)

¼ Corner W. ¼ Cor. 7 Kalmar 107-15

11/15/78 Dug a small hole with the jackhammer on the West side of Kerr's C.I.M. (head broken so removed it). Found the CIM over a pipe driven on the South side of a limestone of about 12" length and rectangular shape in black original soil.

5-4-1980 (1980 Reman BK) Took reference prior to road grading
1" x 35" Sq pipe w/cap 12" deep E 74.83
1" x 35" Sq pipe w/cap 12" deep N 74.41
The ¼ Corner is on line between these two irons which is the N. line of C.R. plat #20 on the East side but the West iron is not on the land line in Dodge Co. but an extension of E-W ¼ line Sec. 7.

Govt Meas Kalmar, Kansas 1854

10" See [illegible] [illegible]

Black Oak 14" 15° W 1016 links

7-11-85, W.¼ Cor 7: Referenced corner before C.R.5 construction

I Set P.K nail 214.29 South of the corner in the ℄ (found) crack at the end of previous concrete construction and on line to a 5/8" re-rod 429.4 South of the PK (rod 29.3 SW'ly of ℄ C.R.5 on curve from N. to SE and 42.45 NE of the center of pp # 47312)
Note: line from PK to rod passed .13 west of P.T.

II Occupied P.T.
Meas. North to W¼ Cor 7 - 384.24
Meas. South to P.I. - 623.66
∠ Rt W¼ Cor 7 to P.I. 179° 59' 44"

See also 5-4-80 reference.
8/7/89 OHD SET 5/8" BRASS PLUG IN ℄ C.R. #5
CHD DISC IN P.P. NW 66.53'