1 4-23-69 set short CIM M&L 2634.4 (1)
#751504

1/4 corner 15 - 22. Kalmar 107-15

3-1873 Hanter P217 no 221 $15 J Fairchild, C Finn.
Corner in 1½' washout in road. set temp stake Midway only 39.95.
-1/16 east. set stake Midway 19.97½. To stake in mound
at SE corner 15. did not run line only wishing to
establish line dividing SE 1/4 15 only meas. South line 15.

4-1969 J Kerr B98 P49.
Run & meas line between 15 and 22 after setting NW cor 22.
Meas. 5268.8. set CIM shorter in black top road
M&L 2634.4 came 2.85 east of Center line - over.

Rod driven by county as 1/4 corner lies 2.85 west and 5.7' south of C I N at M & L.

- drive in power pole # 21561 - E15-15 1.0 - 10.0
4' south of E 46.6

-16 east found pipe set by surveyors as 1/16 cor. true corner comes .33 east and 2.42 north of pipe

- meas pipe from east 1317.73 actual 1/4 mile 1317.4. line of pipe N & S - pipe lies 2.42 too far south.

C.H.D. 1927 Book 51 P.69
No Stone - Cor. Assumed To be in middle of Road
Ties: Sp. in 10" oak N.W - 81.3
Sp. in 12" oak - N.W. - 58.3
Sp in Cor. f.p. - East - 25.4

Kalamazoo ¼ corner 15-22 #751504 | 2
Govt Notes Kavanagh 1857
40.00 S-E from ¼ sect post
West on true line between sects 15-22 N 9° 15' W
40.00 Set ¼ sect post in mound with charcoal
pits, charred stake & Osage Orange sects
N E & S. W.