8-26-1965 set C/M. over 3/4"x14" iron with stone #1 south of corner. #751606

1/4 corner 16-17 Kalmar 107-15

6-1885 Hunter P 397 no 387 S 17. D King.
found stone set in mound. still plain, from orig stake.
-1/16 south set stone M & L. 19.96 1/2.

Co Hwy Dept claims found & used corner.

8-1965 J Kerr preserving corners.
found stone 3x5x14 by very old corner post.
set C/M over 3/4"x14" iron with stone south of iron
mer

- Meas south 2633.45 recorded 2635.4.

1¼" conduit pipe up 18" S W 0.7'
40 D in each side knarly box elder up 4' S 16.75
120 D in 20" oake on south side up 2' W 47.3.

1890 J Fraser unrecorded survey. found stone, no desc.
set stone south M&L 19.96 ¼ 1317.5 2635.0
set stone north M&L 1314.55

12-9-70 Do surv. run line from point M&L 26 27.3 at ¼ 17-18 east over random nail in tree knot at 1991.88 inters line from ¼ 17-20 at 2627.83 R 2626.14, corrected line came 1.3' south of ¼ 16-17. or intes 2628.48
- ag E side SE ¼ 17 Meas 2' less than record seems unlikely that W side " would be 2.34 longer. leaving W ¼ 17 still wrong.
R Center north 2624.16 - traverse N 26 11.39 + 5.92 - 2617.31 - 6.85 short
Center 17 must be south of point where line would place it.

#2

1/4 Corner 16-17 Kalmar 107-15

#7516O6

12-4-75 (1/16N) Dug 3'x5' at computed corner location. Covered line from both theoretical location and finial location of Sec. Cor. 8-9-16-17 to north. Found nothing.

Govt Mons Kan. ck 1854

90.00 Set 1/4 steel post - in mound with 1-inch pits, charred stake & Osage Orange scrib NE 1.5 ac.