1 8-13-70 set C/M over org stone & iron guards.

1/4 Corner 21-28 Kalmar 10 7-15 glass (1)

5-1872 = NOTE: date Hunter P197 No 207 S21 Simonson, Rickert #752104

Corner gone, no evidence or knowledge so set corner, a stone 3x8x15 with small stones at bottom.

M & L. 39.93 (2635.38') at N 89° 40' W

Bearing line north on 1/4 line N 28' E 1317.69

-1/16 east set stake M&L 19.96 1/2. which came 2 lks east of oak post at miters of fences.

6-1876 Hunter P296 No 291 S21 J Murry, Jr Caulfield found stone in center road with stake by side P 197.

(over)

– North set stone 3 x 4 x 18. on line and 1/4 dist to Center 21 9.97 1/2.

– then set stone as 1/16 north another 9.97 1/2. (658.35') then another 19.95 to Center 21. a stone P197.

1968 Cedric G Sanhilon meas S line 21 C IM to C IM. 5283' and set nail at 2640 (from east). To split line for point intersection. did not find monument R5270.68 1972 C

8-6-1970 Co surv. run & meas south line sec 21. on ⑤ N 43 17 for line meas on direct line 5281.12. found cedric nail .29' east of midway and some .5' north as point set in line fence only. 1972 record is 5270.76 – found 1/16 fence N & S west of SE 21 at 1323.85 To 2nd bard-wire from bottom running north & corner post R. 1317.7 – nail in road set by Cedric Liberty 2640.27 then 2640.85 to C IM at SW 21. – set small nail on true line at 2640.56 which came in line fence east and 3' west center road

see Card # 2.

#752104

8-6 Card # 2 1/4 21-28 Kalmar 107-15 (2)

RP to nail - will set CIM here if unable to find stone set 1872 P 197 Make some 10' bnes record which does not hold measured survey 1 S 21 Act 2640.56 R 2635.38 (T.A. 1872)

- pages Cap on NW side PP 21619 NE ~~65.0~~ 66.19
- head & lag screw on N side corfence post E ~~46.0~~ 46.25

will use tractor to look for corner stone or remains

8-14-70 Co Surv. dug with tractor found stone 2.8' deep in 20 minutes. stone witnessed by farmer Glazemaker on W side road set 1/2" rod on W side 5/8 on E side stone with end of barb wire reel draped over stone set CIM & glass above.

see change in RPs above - corner 1.70 south of main fence east.

- eyeball line of power poles north-west edge witness pole looking with rest of line (straight line) 35.85 pole line south crooked.

OVER

line now measures .4' longer on each half. Cor. 2 W of mid-way.
East 2640.76 west 2640.36 and 1.26 south of
direct line as C I M's are now set
corner at least 3' west of center road.
Cor. Notes [illegible]
40.00 set temp. ¼ set post
West on true line between sects 2, 11
40.00 set ¼ sect post in mound 1/2 x 1
chiseled trees & bears, charcoal stakes
Osage Orange trees NE & SW