X 11-27-73 set 1"4 x 30" ± pipe over Markin clay. (1)
tested by line from south and records.

section corner 22-23-26-27. Kalmar 107-15

5-1872 Hunter P 204 no 212. S 26 J Hogans, J Duffin
found stake driven even with surface at intersect of
fences agreed preserved by John Duffin. #752305
-1/16 east set stake. 19.83 1/2. (1309.11

5-1885 Hunter P 396 no 386. S 26 J Graham & others
found stake by side of corner post P 212.

6-1901 R Fraser P 699 no 618 E 1/2 27, W 1/2 26. Jones, Larson
found stake running to a point. agreed by Mr Johnson owners
of lands on North side.

(over)

-1/16 each meas to Hunters stake 19.83½ but varied 6 links (didn't state which way.) If 19.89½ (1313.1) was Hunters 1309.1 would more closely agree with 1967 meas of 1315.0 see 23-24-25-26.

-1/16 west set stone M&L 19.83½ (1309.1) JKerr.
6x9x18 - found stone 1967 - meas 1310 ±
found in fence corner area by large tree south of corner post in angle of fence intersection and brush. undisputed alone.

1/16 W. OF SEC. 22-23-26-27 KALMAR
6/6/86 FD STONE ON S. SIDE MOST SOUTHERLY C.P. AND ON N. SIDE TREE STUMP

6/12/86 SEC COR 22-23-26-27 KALMAR DUG FROM ½' S. OF PIPE USED AS COR. TO S. 4½ FROM PIPE & 2' EAST & WEST OF PIPE. FD BOTTOM OF C.P. TO BE 1.4' SOUTH OF PIPE DIGGING IN OF THE POST DISTURBED THE SPOT 2' S. OF PIPE FD 2½ TO CLEAN YELLOW CLAY

Lee Land #1

Card # 2. 22-23-26-27 Kalmar 107-15 (2)

Corner post used in surveys for alignment and sub-division of brg plats. Corner now needs #752305 accurate and fund location - 1/16 stone west found pones post location very close.
11-27-73 using C/M at 26-27-34-35 and wood stake found. 10-30-73 at 1/4 26-27 and assuming Perrys N & L. 39.80 2626.8 to be equal N & S. Meas electronic line and found. C/M to stake 2633.32 and dark area in clay just north of corner post mentioned set 5266.0 a brg. & errun but would set up E-W 1/4 line of Sec 26 perfectly as well as post brg used at 22-23-26-27. set 1/4 x 30" pipe at this corner and

Moved C/M at 1/4 26-27 7.1 north to come .32
south of stake making line between 26 and 27 a
perfect N & L qtr recorded but at 2633.0' not 2626.8'
and on line fences E-W-S as recorded.
Note- 1/16 pipe between center 26 and 1/4 26-27 now out of line
but midway ±
Corner .25 north of nail in center corner post (nail removed).
9.75 east to top of 1st steel fence post of fence east.
Corner accepted as final until proven otherwise
Set 48-in Kappler 16 oz
60.00 set post for corner to stone
22-23-26-27 found mound with brass
pins, chiseled stake 1 orange orange mark
at each angle

Sec Cor 22-23-26-27 (3)

#752305

8-4-93 Fd 1¼" pipe used in other surveys we bent in the pipe Top and put an Aluminum Cap in pipe w/Post & sign .5' South