6-9-72 set C/M over 1¼" x 2' pipe by lines & meas from N & E. #752404 (1)

¼ corner 24-25 Kalmar 107-15

no records - no evidence - no knowledge.

8-1967 J Kerr. meas from NE 25 west in attempt to find NW 25 or re-locate. run no line - east ⅔ of line clear. west ⅓ drainage ditch & weeds on line. - set 120 D just south of large corner post & well preserved fence running north - common land to south set at 2631.5 - set lath sight on post for aerial line. - continued west to ℄ road where corner finally set 5273.0.

(over)

April 1963 R.C. Compton Pg. 72 No. 103 Shows ¼ Cor. used to set Center Sec. 25

on aerial transit line from NE 25 over above corner past sight the line would come 24.3' north of fence line west at NW 25 where corner was finally set. Making corner past at 1/4 24-25 12.15 north of direct line and 5.0 east of halfway.

---

corner used S-1880 Hauley surveyed survey P111 No 358 old book. He used corner to set stone 9314.4 east M&L 1967 Meas from ¼E24 to post 2631.5 record 2628.8.
10-1968 line from center 24 & 1/16 stone north indicates corner east of post by 2.55' as line from corner post to 1/16 stone came .85' west of center stone found.



Card # 2. 1/4 24-25 Kalmar 107-15. (2) #752404

6-9-92 Co surv. Meas west from E 24-25 (meas from 3/8" rod set 100' W of then C/M. Lake broken & removed - found new N-S fence at 1314.4 ± Record

dug & found boulder with 3x8x14 L stone not vertical by it. Could not be where Hanks placed it in 1880 as wires were near 2' below but believe it same stone. found defunct post hole with bark etc 3' deep. about 18" or so south of new 6" corner post. - set steel fence post in hole and used as line to project west.

- dug entire area east of Corner fence E-W-N at 1/4 24-25 To clay found nothing. - projected line from east Came under fence. so set corner (over

set 1¼" x 2' pipe below C/M on line from east and 2.55 east of joint 15' E of offset lath stake in fence used in 1968.

Corner came under fence and of course 2.5' E of corner post. C/M log just below flush with surface in area and small stick part of fork handle by corner - rag on wire above.

Consider corner found meas E 2628.5± almost record.

Gov't Notes Kanick 1951

40.00 set temp ¼ sect. post
West on true line between sect. 24 & 25 T 8 36'
40.00 set ¼ sect. post in mound with bench
pits, charred stake & orange orange seals
WEISER