4/2/89 FD ½" PIPE/CAP # 11622 #752709 (1)

¼ corner Center 27 Kalmar 107-15.

1-1870 Perry P92 No 136 S 27 town board. road survey
found stake set ± 4-8-1868 with B trees.
by R. Perry
– north set stakes for road line every 40 rods.
Meas 39.89½ total to N ¼ 27

4-1870 Perry P106 No 145 S 27. PW Fritts.
found stake set 4-8-1868 set stone on N side.
Made mound with stake in center over stone.

6-1901. Robt Fraser P699 No 618 E½ 27. W½ 26 Jones Jarson Ener

TH field BK of Rd Surveys (C A Armstrong's) Stone, pitch pins by Perry
BTs N7¼E 62 lks T.J.O. – N46½°W 4.00.70 – S45½°W 6.00.82 lks

found limestone center road & B tree.

— 1/16 east. set stake M & L. 19.89 3/4.

Mr Larson owner he will set stone here.

9-1924 Co H D B 39 P78 found stone.
RPs Hubs S E and NE .50.0

8-1927 Co H D B 51 P67 found stone with hub and nail.
ap in 20" oak NW 88.2 — 16" oak WNW 45.6
~~28~~" oak SW 54.9 Meas south - 2649.7 to stone
Meas north. 2629.9 to stone. total mile 5279.6.

Note B 270 P1 1962± mile from stone 1/4 22-27 to assum cor
at 27-34 5275.6 - Sanborn set record reproduction corner.
3.67' south & county lies making 5279.3.

April 6, 1976 dug with Jackhammer - found Co. H.D. 120 spk & accord Hub
also found piece of Limestone lying down - spike is about 1.2' w. of 1/4 line & [redacted] in
line fence To E.

1/4 CORNER CENTER 27 KALMAR 107-15 (2)

4/2/89 FD ½" PIPE / CAP #11622, 4" BELOW SURFACE OF C.R. #3 SET CONC. NAIL AT SURFACE FOR AERIAL TARGETING. THERE IS A P.K. NAIL 1.00' EAST & 0.10' NORTH OF PIPE RP. #752709

CSD IN C.P. EAST 50.07'