7-14-77 CTC

#813405

section corner North 3 - 4. Quincy 107-11.
and Wabasha county.

12-1891 Chas Fraser P 467 no 449 S 4 Geo Wedge.
found fence post set by Mr A Ferrier in center of
original mound. when stake was standing plain.

1/16 cor south - set stake on line and prop dist. line overran.
56 1/4 lks. Meas from corner S. 20.25 then 20.28 1/2 to cor.
between 3-4 a stake reset by B 13365 bros.

1/16 center NE 1/4 4. - set stake M & L. 20.16 1/4 on E W 1/16 line.

1/16 cor on N-S 1/4 line between N 1/4 4 & center -
found stone and stake set by Mr. Bostwick a surveyor

(over)

from Wabaeta County set years ago when corners in place.
All corners gone in West half section 4.
accepted stone & stake as corner for work at hand
land very rough & bushy. Nearly impossible to work in.

Gov't Notes: Sept. 1853
Set Post & drove charred stake, built mound with trench

7-14-77 Accepted the corner post as per Tom Fraser Survey No. 449. Set a CTC /p² as the corner on the SE side of the corner post to fences N and East Sp in SE side 2" Black Oak NE 20.00

RP's: Sp & CSD on E side blazed 7" Burr Oak 4' East of the fence N NNE 26.65
Sp & CSD S. side blazed 14" Black Oak NE 32.77
Sp & CSD W side blazed 24 Black Oak (West of Stone) NE 17.28