9-5-79 CIR #820705 (1)

X section corner east 12-13 Farmington 108-13.
6-1851 Horton P85 no 130 N½13
Meas west 39.90 (2633.4' south 39.73 (2622.18'

4-1925 Co H D B 44 P 70 found stone mon. in place
in road intersa Sta 648+42.6 Meas west 2636.0
to ¼ 12-13 as used corner lines [redacted] ℄ N-S Rds
Hub in fe. line NE 43.3; same SW 53.9, same NW 52.4

9-21-70 Co surv - found ¾" rod in center intersa of roads
road fill 6' on N side - 4' on S side road!
MHD - drec in Tele pole SE ~~78.85~~
8" conc MHD with 3" cap marked 81.38' - Sta 667+52.4 SE ~~81.35~~
Cross in S end conc curb 30" top ℄ center SW ~~48.35~~
" " N " " " " " " NW ~~52.25~~

(over)

punch mark in clamp lug top S end culv flange SE ~~53.56~~

" " " " " " N " " " NE ~~61.25~~

Set by John Bull (9-1853)

50.00 Enter Prairie bears N.E.

80.00 Set post and drove charred stake Cor. to Sect. 7, 12, 13 and 18. Built mound with trench per instructions Planted S E. Osage Orange N.E. Apple Seed.

9-4-1979 Dug into the backhoe centered over a point set up from RPs taken in 1970. Found a 3/4" iron beneath the blacktop over another 3/4" x 17" iron. At 5' deep we found a 1" x 2" hub with a 1/2" x 12" iron and a square 1/2" x 2' iron. At 7 1/2' deep we found a 9" spike and hub and at 8.3 deep we found a 10" x 10" topped by 15" long boulder in black soil beneath the old road and into base in clay (See 1979 Remon Book for small differences in the monuments)

Section Corner East 12 - 13 Farmington 108-13 (2)
#820705

(Continued) There was an old stake on the West side of the stone. We put a 3/4" x 17" iron in the stake hole and set the stone back.

9-5-1979 Set a CIM over a 1/2" x 19" iron over the boulder found. The corner is in ℄ of road E-W-N-S

RP's:

MHD in telephone pole SE 78.88

Punch mark in lug on top South end culvert SE 53.56

Punch mark in lug on top North end culvert NE 61.27

Chiseled cross in top South end 30" concrete culvert SW 48.57

Chiseled cross in top North end 30" concrete culvert NW 52.38