#823105

7-1-1966 set CIM on ~~engraved iron~~ ~~5/8" rod~~ (1)
7/20/88 RESET CIM FROM TIES OVER NOTHING
section corner township corner. NW cor 6 Viola 107-12
SE cor 36 Farmington 108-13 - Haverhill NE 1 107-13.
5-1872 Hunter P202 no 211 d 1-2 J Moody, C Raymond
found hole lined with bark after running line from
NW cor 1 over N'ly 41 and doubled distance 39.85 (2630.1'
- Meas south 39.84 to M & L. d 40' W (N 89°5' W

11-1886 Hunter P416 no 405 d 36 W. Leade, C Raymond.
found engraved stone monument set several years back.
- Meas north 40.01 to stone & iron rod set M & L.

7-1966. J Kerr dug extensively for corner. large culvert
in place diagonally across intersection NE to SW. found. Dug
TWP Corner Now

stone concreted into headwall culvert by road crew.
replaced corner by projecting line from NE 36 over E 1/4 36
and intersecting line from SW 35 over S 1/4 36.
- meas north 2635.6 to stone found (now CIM) then
2638.9 To NE 36 (now CIM).
- meas west To stone & iron recorded and found (now CIM).
2636.4 then 2633.4 set on town line at distance
recorded by Hunter P 416 which checked by 1/16 fence north.
RP to township corner. a little south of center crossrode 7/29/88 10-2-72
Disc in big power pole. SW ~~64.36~~ 64.69 ~~64.71~~
" " " " " SE ~~47.3~~ 47.26
Cross ~~cut on top of~~ headwall of catch basin west end 5' road
culvert. in ~~low~~ center culvert. SW 42.2 42.18
- 1/16 West. set 1/2" x 2' rod. set at 1318.2. west of town corner
RP. Disc small tele pole NW 41.6 - center road - Must go 1.66 North

#823105 (2)

Card # 2. Township corner SE 36 Farmington 108-13
NE 1 Haverhill 107-13, NW 6 Viola 107-12
10-2-72 set T-2 on C/M at E 1/4 36 and found it
to be .14' east of direct line.
E meas north 2639.84 1966 2638.9 H 1882. 2640.66
" south 2637.07 1966 2635.6 H 1882 2640.66
final line from W.
Twp corner now 14" ± deep. with added grade.
Dice in log power pole SW. 64.71. 1966 64.36
Dice in power pole brace anchor only SE 47.26. 1966 47.3
Cross in center W lead wall of catch basin SW 42.18 1966 42.2
suggest at 1/16 rod west to find rod and reset on true line
on remeas & run line - twp corner should go south 2.77 for records.

set by John Ball 9-1853

80.00 Set post & drove charred stake Cor. to Township 107 & 108 North of Ranges 12 & 13 West built mound with trench per instructions. Planted, 3E Osage Orange, NE Appleseed

7/28/88 FD CIM GONE (7/28/88) SET C.I.M. BACK FROM TIES NEW RP P.K. NAIL IN TOP OF GUARD RAIL POST N.W 30.63'

(7/28/88) CIM TAKEN OUT FOR REPLACEMENT OF CULVERT RUNNING DIAGONALLY ACROSS THE INTERSECTION, SET 60d SPIKE FROM TIES TO P.P. S.W. & S.E., AFTER TRAVERSING DECIDED POSITION CORRECT., CORNER IS E OF ROAD E & W 1' EAST OF E ROAD SOUTH & 2' EAST OF E ROAD NORTH

C.H. DISC IN PP # 20910 S.E. 47.26

C.H DISC IN PP # 24391 S.W. 64.69