#831505 (1)

6-8-1968 set C/M over ½" x 2' rod.

section corner 15-16-21-22 Farm. 108-13.
set by Wm Kerby 5-1857
5-1900 Ch Armstrong P666 No 592 L21 J Zhoening
J Weike.
set limestone 3x12x19 as corner.
after meas NW 21 to NE 24 east 4 miles.
and meas NE 16 to SE 28 south 3 miles
- meas west 79.965
- " east 80.145
- " north and south 39.993

He found old stake hole when dug at this pt.

5-1900 Ch Armstrong P667 No 593 L15 A H Kruger.
found corner, used to meas point as L¼15 for
line North to set Center 15.
Corner

– Meas east 40.0725. as in P 666.

6-1966 JKarr.
set C/M one ½" x 2' rod at point set as corner in Ruckart survey some years back. 1962.
dug 5' wide to clay entirely across road. after made from known ¼ cor west to long established ¼ fence each. found spot possibly corner have been where stone set about midway of these ¼ fence.
this spot 3' west of west edge traveled road in ditch slope. about .6' north old woven wire fence west
– no trees, no culverts, no poles no corner posts of any stature to reference to.

#831505 (2)

Section Corner 15-16-21-22 Farmington 10S-13

80.00 Set a post for corner to sections 15, 16, 21 & 22 in mound of Earth & Sod deposited charcoal made trench & pits & planted Osage Orange Seed on N.E. & S.W. sides of trench.