10-11-1965 set C/M over ½" x 12" rod. (1)

#831606

¼ corner 16-17 Farm 18-13
Set by William Herby 5-1854
5-1878 Hunter P 347 No 340 S 17 H Taylor
H Beckett
S Carston

Corner came in road on "point of a hill" which had been cut down several feet & corner destroyed. settlers aver that fences east & west were set opposite corner when it was standing. accepted fence lines as northing & southing to set center section.

– meas south 39.96 (2637.38'

5-1898 H Fraser P 630 No 570 S 17 S Martin
used assumed corner as in P 347. Wagnor.
Meas south 39.90 (2633.4' (over)

this meas 6 lks shorter than Hunter but from center south the meas was 4 lks shorter so corp nearly same

10-1965 J Kell.
road still about same as described a narrow township road graded down even more than described.
- run N-S section line between corner accepted in Potsdam road and corner set as SE cor 17.
- set C/M over 1/2" x 12" rod M & L 2632.65
  corner down 9" to top of monument.
- Corner lines with fences E + W.
- " lies 1½' to 2' west of ℄ traveled road.
- Blaze on N side 8" cedar cor post E 34.0
- 1/2" x 24" rod up 3" in fence line E 50.0

1/4 Corner 16-17 Farmington 108-13 (2)

40.00 Set a chared qr Sect. post in mound of Earth & Sod made trench & pits & planted Osage Orange Seed on E & W sides of trench. #831606