/ 5-18-76 CIM on original stone #831906 #1

1/4 corner west 1/4 19 Farm. 108-13.
east 1/4 24 Orono. 108-14.

5-1874 Hunter P308 No 302 S 24-25 Rowley, Webster Standards
corner gone no evidence or knowledge

- set stone 4x6x24 M & L 39.83 1/2. 2629.11
- 16 north set stake M & L 19.91 3/4. 1314.55
- 16 south " " " 19.91 3/4. 1314.55
- 16 west " " " 19.93 1/4 1315.55
- 16 Center NE 1/4 24 set stake M & L 19.81 on N-S 1/16 line
- 16 Center SE 1/4 24 set stone 7x8x20 inters lines

1-1878 Hunter P327 No 321 S 19. H Blohm.
found stone P 308 no mene used to set Center 19.

2-10-76 Set nail M&L W. Sec Cor 19-30 to corner post at N. Sec Cor 18-19
Nail on E bank of wash running S into E-W creek and approx 4-7
S. of E-W Fence.
R.P.'s Spike S. side blazed 4" Box Elder NE 1.35
Spike W side 6" Box Elder NNE 3.32

Set by John Bull 10-1853
40.00 Set post & drove charred stake for qr Sec. Cor.
built mound with trench per instructions Planted S.E. Osage
orange N.E. Appleseed.

3-31-76 Dug at M&L location. Found post stub 8" deep 1½' ± S.
Also found wire running S and E so probable
corner post.

5-18-76 dug and found 4"x6" topped limestone 2½' deep.
Stone 1.1 N and .3 W of M&L location to corner
post at NW 19. Drive pipe on N. side and rod
on S. side. Set CIM over stone with steel post on NW
side. Corner 9' E center of ditch W and 30' N
of center of ditch S and 7' S of E-W fence.

#831906 #2

¼ Corner	West ¼ 19	Farmington	108-13
	East ¼ 24	Oronoco	108-14

RP's Spike and CSD in 7" Elm SW 79.25
Spike and CSD in 4" Elm (mud setting) SW 48.16
CSD in corner post N 201.15
Spike W. side 6" Bof Elder NE 2.62
Spike S. side blazed 4" Bof Elder SE 2.12