X 6-28-1974 Set C.I.M. over 3/4" x 18" Pipe #832104
11-16-95 CHD SET 1" SQ PIPE W/CAP (1)

1/4 corner 21-28 Farm. 108-13.

5-19 00 Ch Armstrong P666 No 592 L 21 J Zhoening J Zielke

found stone midway L W cor 21 and
corner set as L E cor 21. - 3 1/2 links south of
direct line between section corners.
- Meas east & west 40.105

---

stone found. 2.3' south of section line
either county or Mc Ghie
Spike power pole NE 6100.5
" tele NW 5209
"Same as 21-22-27-28 RPS.

MARCH 1973 TAYLOR - SET IRON midway ℄ on LINE
2640.48 - 2640.48 DIST-O-MAT 1.2' EAST OF FENCE TO NORTH

6-28-74

Remeasured the Sec. line between 21 - 28 +
Set a C.I.M. over a 3/4" x 18" pipe m+L
by elec. meas. at 2640.27. The pipe set
by T. Taylor was .23' to far E. by our
meas. T. Taylors crew however did Not
have the southeast cor. only a point
from the R.P.'s

~~R~~. R.P.s to 1/4 cor.

Nail E. side P.P. # 34903		South	46.32
" W. side 5" cor. post		North	51.10
Punch hole top E. end 18" C.M.P.		N.E.	52.64

#832104 (2)
108-13

1/4 Corner 21-28 Farmington
Set by William Yerby 5-1854
40.01½ Set a gr sec post in Mound of Earth & Sod. deposited charcoal made trench & pits, planted Osage Orange seed- N & S.

8-2-93 Set Ref pipe w/cap & Rt 180° 02' 21" to main Radio Tower. Tower SSW of cor. Dug pipe down in Corner of field. T @ Ref Pipe to 1/4 cor 21-28 VA 91° 51' 28"

Slope 55.58 Hor 55.56

7-14-94 Comm to South block Tower will set cap in fall. We set Conc Nail @ 1974 Tie location for Temp Cor location

11-16-95 CHD SET 1" SQ PIPE W/CAP