8-8-83 C7c1p2

#832305 (1)

section corner 22-23-26-27 Farm 10 8-13
Co. H.D. Bk 58 p.9 - assumed corner
No records - also J Kerr 10-1946 B32 P28 same RPS
Co Hwy Dept. used B-199 P4 (no history)
assumed corner set 1" x 2' iron shaft.

Spike	tele pole.	SW	35/5	gone
"	power pole.	NW	45 E.	1983
"	cor fence post	NE	50.5	(over)

5-1900 Ch Armstrong P666 No 592 S21 J Thoeming
in Mtge from SW21 to SE24 to set SE21 J H Lehe.
placed above corner by Mtge at 80.20 to SW22 ≡ 80.18 to SE23.

Meas - south 2643.71 to rod set N & L. (J Kerr data also.
Meas east 2639.35 to pipe set N & L.

Meas south ~~5289.8~~ 5279.8 B 199 P4
Meas north 2639.6

B 238 P3 Meas west 5283.54. Assum R 5293.2.
Meas east 2631.53 ~~Top~~ assum 1/4 corner thence
2648.1 To 23-24-25-26

Assum R 80.18 5296.88 5279.63

Set by William Yerby 5-1854
80.00 set post cor to sec 22, 23, 26 & 27 in mound of earth & sod deposited charcoal Made trench and pits planted Osage Orange Seed NW & SE.

1930 Co. H.D. Bk. 58 P.9 Corner Assumed 289+94.55
Ties to Assumed PI (called Sec. Cor. 22-23-26-27) PI- △ 90° 32' RT
Cor. fe. post - NW 36.95
Cor. fe post NE. 36.75

#832305 (2)

Section Corner 22-23-26-27, Farmington, 108-13

6-14-83, Sec. Cr 22-23-26-27: Found 1" rod down 3", ½' West of ℄ N-S C.R. 11 and in ℄ C.R. 21 E and West. Raised to road surface.

RPs:: Old CHD disc in N side pp# 19983 NW 105.01
Old CHD disc in NW side pp# 19982 NE 71.41

7-11-83, Sec. Cor. 22-23-26-27: Dug from a point ½' East and 1½' North of the 3/4" iron at the road surface shot here, South for 8' and West for 9' by 7' deep. Down 2½' and in a crushed rock road we found 2 large spikes together .48 North and .21 East of the 3/4" iron. In the same crushed rock road we found a 1"x21" shaft ~~set~~ (removed) set by John Kerr in

1946. Said shaft 2.79 West and 3.35 South of the 3/4" iron t.p. Dug down 5' to black dirt. Found a limestone 3 1/2" x 5"/10" x 18" with a 1 1/4" x 2' pipe standing on its South side and 2 1" x 2" laths over the pipe and stone. The stone 1.62 West and 6.10 South of the 3/4" iron. Drove the 1 1/4" pipe deep (top down 7') at the stone location and set the stone on the East side. Could find no stake with the stone. 1 1/2 to 2' of black dirt here. Found nothing further. We were concentrating the dig South and West to dig towards midway between the fences at 1/4 Cor 22-27 and 1/4 Cor 23-26 and midway between the fence a 1/4 Cor 26-27 and 1/4 Cor 22-23. Set a 5/8" smooth rod back at 3/4" iron location as probable CHD P.I. (1953)
(See Ranger Book for local RP to pts Fnd)

#832305 (3)

Sec. Cor. 22-23-26-27, Farmington, 108-13

8-8-83, Sec. Cor. 22-23-26-27: Set a CIC/p² at location of stone found 7-11-83. The corner is 5½' South of the ℄ of the E-W road and 2'± West of ℄ N-S road.

RP:
CSD in pp# 19982 NE 76.85
CSD in pp# 19983 NW 109.43
Punch hole in South end 18" C.M.P. SE 40.04

7-30-93 Set 1" sq pipe w/cap (Ref Pipe) NW of Corner in field drive ± 45' west of ℄ CR #11 & Rt flashing light on top of shortest of two towers SSE of corner.

333° 57' 55"
VA 89° 34 50"
Slope 77.26 Hor 77.25

7-14-94 SET 1" SQ PIPE W/CAP AT 1993 REFERENCED LOCATION.
THE CORNER IS 2' WEST OF ℄ CR #11 + 5 1/2' SOUTH
OF ℄ CR # 21
CHD DISK IN P.P. # 19982 NE 76.78