#832506 (1)

11-20-1963 ~~set C/M over 1/4 x 18" pipe.~~
10-5-1972 found recorded stake left C/M as it
1/4 corner. 25-26 1972 Set C/M farm 108-13.
set by William Kerby 5-1854

No records -
school district - old no. 81
in NE corner of SE 1/4 of 26

Deed book 40 P144
Ernest De Wilz 4-28-74

Commat NE corner of SE 1/4 Sec 26 for beginning.
W 11 1/2 rods. 189.75' thence S 14 rods 231.0'
thence East and North to beginning.

11-1886 Hunter P416 No 405 S 36 N Lucas, E Raymond.
used corner and 1/4 35-36 to get measure to set
N & S for 25-26-35-36 or short 7 lks for mile.
so meas south 39.96 1/2 - no desc. of corner. 2637.7

(over)

1¼ x 30" pipe in place as corner.
11-1963 J Kerr. set C/M over 1¼ x 18" pipe as corner in place of 30" pipe.
Spike in creosoted corner post E 35.3
" " power pole. ESE 156.7
Center 20" spruce SW 39.1
Corner lies 3.5' south of fence running E & W

10-1946 J Kerr. B 32 P 28 J. Harvey survey.
set 1¼" x 30" pipe as corner N 0 L 2640.0
3' S of fence west 22.3' E of fence W (likely road Fe.
- used to set 1¼ x 4' pipe as center 26 - 1½' W of fence corner.

Card # 2 1/4 25-26 Farmington 10 8-13
#832506 (2)

10-5-72. Elec meas from C1M at 25-26-35-36 To C1M at 1/4 25-26. 2638.97. JKerr 2640. Hunter 26327

- found Hunters recorded iron at 25-26-35-36 4.34 E 5.94 N & C1M reducing meas to 2633.03
- dug and found Hunters stake or "1/4 post" in Center road at 1/4 25-26 3.4' E 2.26 N

meas now 2635.29

- C1M 3 at both places likely will not be removed but any future work may use true corners.
- 1/4 25-36 will use iron to set corner N & L - final
- 1/4 35-36 will use iron and meas north to set corner - final

10-6- used as above

10-5-72. dug with tractor from CIM north 6' 3' west 4' east & found near square hole in lower soils, a pasture post hole with 1½" definate hole over 12" deep with wood remains in hole.
drove 2"x2" hub 2' long a few inches in stake hole. and placed it plumb and packed dirt evenly. set no iron or did not remove CIM.

Meas south to iron found.		2635.29
" " " CIM.		2641.23
" " between CIMS.		2638.97
Spud in " power pole.	ESE	158.22 CIM 156.7
nail in knot on N side pine.	SW	43.37 CIM center tree 39.1
½" iron set as prop corner old school 2'S 4'W.		36.4 CIM 33.

#832506 (3)

1/4 Cor 25-26 Farmington 108-13

40.00 set a gr post in mound of Earth and Sod deposited charcoal made trench & pits planted Osage Orange Seed E & W.

7-20-83, 1/4 Cr 25-26: Dug hole to set monument at Rogers 1972 loc. by R.P.'s. Found spike standing good down 10". Spike .10 South and .09 West of the t.n. set by R.P's. Assumed spike to be Rogers and set a 20" CIM over a 1¼" x 15" pipe. Removed Kerr CIM and pipe beneath which stood 3.32 West and 2.27 South of the CIM set Corner in ℄ N-S road and in line place West and true line E.

RP's: CSD in pine (NW side, s'ly of two) SW 49.77
CSD in South side brace post W 45.08