X

#832605 (1)

section corner 26-27-34-35 Farm 108-13.
11-1877 Hunter P324 No 318 & 34 A Domke & others
found stone set at center crossroads by Mr Lindsley.
where org stake stood.
- Meas south 40.05 To stone set be testimony
of Mr Lindsley. } Co. RD. B. 199 p.4 (1953±) does not identify
Corner as Section Corner or mon. found.

Co Hwy Dept B. 328 1967
Zinc tag in 1930
? boulder with 1" drill steel riser - 1961. drill steel -

Disc	fence post	℄ E	70.35	1967.
"	" "	N W	62.46	
"	cor " "	℄ W	58.53	58.68
" Hub	power pole (over meas)	N E / S E	59.88	60.0 / 69.95

6-1930 Co HD B58 P8 found limestone on end.
assumed corner at first - meas south 2638.4
Sq in tree maple N.W. 53.1 ✓ — tele pole S W 48.7 ✓

Meas E 2636.5

Meas N 5289.8 to assumed corner

B328 cont - meas east to P.I. 5258.89??
26-27-34-35 is Sta 0+00.5 RPs over).
to PI Co 5258.9
PI in Co 5276.54
Co total 2 miles 10535.44



Hmarks
Hm. 2630.35
Hm 2630.35
Total 5260.7
5266.8
2638.68
5277.36
2638.68
Total Hmarks 1886 P416
10544.16

Govt 79.88 (5272.08)
Govt 80.06 (5283.96)

Card # 2. 26-27-34-35 Farmington 108-13 (2)

10-1946 J Kerr B 32 P28 RPS 827. #832605

a stone with pipe and wagon chain on top.

54.0 NW to bolt & tag on maple stump

45.8 NE to spud in Power pole.

64.0 SE To cross in round conc post.

Meas North 5287.43 to 1" shaft 2' long. or

2643.71 to 1/4. 26-27.

Meas East 5260.7 to limestone with pipe scar.

also set 1¼ x 4' pipe N & L 2630.35

---

set by William Yerby 5-1854

80.00 Set post in mound of Earth & Sod cor to sec.

26, 27, 34, 35 deposited charcoal. Made trench & pits

planted Osage Orange Seed N W & SE.

(over)

Co. H.D. (1953±) Book 199 p. 4 and pages 9 & 10
page 4 does not indicate any monument found nor does it identify this PI sta. 240+43.2 as the Sec. Corner.
Topog. on pages 9 & 10

6-14-83, Sec. Cor 26-27-34-35: Found CHD drill steel down 3". Set nail over iron for traverse. Corner in ℄ rds N-S-E-W.
RP's: Old CHD disc on SE side fence post (there is also a disc on N side) SW 59.18
Old CHD disc on NW side pp 198s3 NE 60.00

7-5-83, Sec. Cor. 26-27-34-35: Dug at drill steel shot. Found it to be only 10" long. Down 1' we found a 3' drill steel .36 North and .01 East of the t.p. Down 2' found and .24 North and .03 East of t.p found a 1" pipe in wagon skein. (continued)

#832605 (3)

Section Corner 26-27-34-35, Farmington, 108-13

7-5-83 Continued: down 3.3 and .18 North and .03 East of t.p. found a 3½" x 9" x 14" limestone (dolomite) Beneath the stone, found the remaining 9" of a 2" diameter stake sharpened to a point with axe marks plain. Stone .28 North and .24 East of the t.p. Drove the drill steel at the stake location (typ down 5') and set the stone and wagon skein on the East side. Dug for the corner found East 2', West 2½', South 2½', and North 5" (bottom of hole). Dug North since we are 5' short of Hunter's measure to stone found at 1/4 Cor 34-35. Hunter's full measure from Sec Cor 25-26-35-36 came 3.9 West of pt. shot. (Set Reinf BK. For local RPs to pt. Fd)

8-4-83, Sec. Cor. 26-27-34-35: Set CIC/p² at location of stake found 7-5-83. The corner is ½' East of ℄ N-S road and in line of ℄ E-W road.

RPs:

Punch hole in North end 20" CMP NW 37.89
Punch hole in South end 20 CMP SW 37.20
CSD in pp. NE 59.58

7-30-93, Set 1" sq pipe w/cap & Rt 180° 01'06" to P.K. Nail in P.P. E.N.E. of Corner (2nd pole on No. side of Rd East. The Ref pipe is ± 10' No. of ℄ E-W Twp Rd & ± 128 East of ℄ CR # 11

↑ @ Ref Pipe
To Sec Cor 26-27-34-35
VA 90° 39' 08"
Slope 129.49 Hor 129.48

SECTION CORNER 26-27-34-35 FARMINGTON 108-13 (4)

7-14-94 SET 1" SQ PIPE W/CAP AT 1993 REFERENCED LOCATION. THE CORNER IS 1' EAST OF ℄ CR #11 + IN ℄ OF TWP RDS EAST + WEST.

#832605