/ - 5-4-1970 huge limestone 5"x8" top with erase #840205
section corner 2-3-10-11 Aromco 108-14
5-1892 Chas Fraser P484 No 461 & 10 John Hickliff
no description of corner but meas south from it to
SE cor. 10 80.26½. set no ¼ corner.

12-1895 H Fraser P586 No 534 & 2 C. Disco, F King
C. Kurth & others
found old corner in pile of rocks, used in several
surveys. undisputed, set long limestone in place of stake.
-16 east set stake N & L 19.76 1304.16
-16 north set stake N & L 20.08½ 1325.6
-16 center SW¼ 2 set marked stake. inters lines
-64 south above 1/16 stake N & L 10.03 -ones-

-64 west of Center S W 1/4 2 stake M & L. 9.87 1/2

5-8 to 11-1900 Armstrong P668 No 594 S 11 Fred Koenig
found stone P 586
-16 south. sandstone 5 x 12 x 14 20.10 (1326.6'
- meas east 39.52 to stone found M & L.

1900 Armstrong P669 No 595 S 10 Chas King.
C Rucker &
F Koenig
found stone P 668
- meas west 19.98 to stone 14 x 14 x 16 set by Rucker
- west set stake at 22.49 1/2 then 17.49 1/2 to
N 1/4 10 boulder. 10 x 12 x 16 set M & L. (2639.34'

6-1902. 21 Fraser P42B S 10 Orono town board.
found stone P668.
-16 south found stone M & L 1322.5 then 13.23.5 set P668.

#840205

Card # 2. 2-3-10-11 Aronoco 10 8-14.

5-4-1970 Co Surv - found limestone with 5"x8" top with cross 12" up bigger below ground. left stone as is. put channel iron highway post North of stone with reflector tin on top - stone lies 1.7' North of large cor post fence E-W-N
- 12" tall oak tree near fence line north 53.4'
- crotch between twin 16" burr oaks in slight notch in fence W 22'±
- run line to C/M at 10-11-14-15
found 1/16 stone between 1/4 10-11 and C/M at 3969.07.
R Wil Fraser 3968 Ch Arm. 3979.8 arm overrun 3.55 per 80 Rd
this stone 6x12" top as recorded. under fence only .17 east of direct line between section corners as run at 50' West.
— Could not find 1/16 stone south so set 3/8x2' bolt on line (over)

and 1/3 meas to 1/16 south of 1323.02 near record
did not honor P42B calling for 1322.5 then 1323.5 to
1/4 10-11 as E-W fence. does 1' south of rod as it is also
bolt lies 2.2' WNW of new cedar post for fence west
- set CIM as 1/4 10-11 in black top on line at ~~2646.4~~ 2646.04

from 2-3-10-11
to 1/4 cor 10-11

Power Dam Survey 1916 found Stone
meas. South 2651.0 East 2610.4
Gen'l Notes M. Kamrick 1854
80.00 Set stone + corner post to set 2-3-10-11
Jack Oak 6 N28 W.05
Bur Oak 6 W65 E 75
Dog Tracks