#840304 (1)

8-10-1966 set CIM over 3/4 x 34" pipe.

8-15-72 found stone corner not set.

1/4 corner 3-10 Oronoco 108-14.

5-1900 Ch Armstrong P669 No 595 L10 C King, C Rucker & Koenig.

corner gone. set boulder. 10 x 12 x 16 M&L

39.99 14" J oak. N 11°45' W 28½ L. (18.81'

- last set turn oak stake at 17.49½ chen 22.49½.

6-1902 ~~Wm~~ Frazer P42 B. L10 Orono town board.

- caption 4-1904. for NW 1/4 10. error in P669. component 0

found stake & stone Bt. J oak. S 78°15' W 28 L. (8.48

- 16 inch drone iron stake in root of cherry tree

M&L. 13 1/4'

- Meas south 2630.5 to stone. -over-

90°0
78°15
11°45

-16 center NW 1/4 10 drone iron stake M & L. 1311.5
on N-S 1/16 line.

5-1941 J Kerr power dam line survey B23.
found stone set 3/4" x 5' pipe as corner! Notes not correct } original 4 pipes unknown.

8-1966 found pipe by RP. to Culv headwall.
set C I M over 3/4" x 34" pipe.
orig RP - cross in east headwall small road Culv. LE 68.15
Nail in hub on N side 12" cherry 37.12 W ~~42.7~~.
Dec in trans line power pole (slope meas) NNW 116.3.
Center top of rotten below but solid corpost NW 46.5.
fence running west north of woods. N 37.0.
- meas north 2650.7. (1966)

#840304 (2)

Card # 2 1/4 3-10 Aroroo 10 8-14.

Staked west RW - 33' W of 1/4 line for realignment of Rock City power poles for grading - did not remove C/M as grading to be done later in summer.

- set one addition RP to mark KPs of road graded.

100' ∠ N to W 46°23 AZ 313°31' to windmill about 1/4 mile in open area to 3/4" x 2' iron in open pasture.

RP to iron - 93.5' E to ℄ present road -
39.5 S to steel fence post on E-W fence.
25.8± "B" pace NW'ly to scraggly bone shown bush.

8-10-72 ran line west on electronic traverse. found 3/4" rod at 1/16. 1.4 N of corner of fence West and south 7.7 W of center 18" elm and about 2.0 N of tree.

(over)

Computed meas to corner from east. — 1318.8 ~
Corner may not be correct No stone found in setting C/M.
Meas west to iron Comp - 1319 ± WF record 1314.
Meas N Power dam 2652.6 J Kerr 2650.7 (1966)
Meas S. W Fraser 2630.5' to stone set intersection all 1/4 Co.
J Kerr Power Dam survey about 5276.37 - 2650.7 2625.67
either center or 1/4 3-10 out of station

8-18-72. dug with tractor, found recorded stone 5.45 west and 2.65 North of C/M in place stone over 5' deep. — set large axle with flange and splined end up on stone. - placed 1/2" x 2' rod over axle and stone found with wood stake. 6' to side - Meas west 2627.08 (single) South 2632.25 North 2646.7
64.0 E to east edge trav road. east 2633.24
91.87 SSE to cross in Culv headwall was 68.15' west to 1/16 1313.86
94.33 NW ly to azimuth rod in pasture was 100.0' then to Sec 1313.72

Card # 3. 1/4 3-10 Oroco 108-14

#840304

(3)

Summary of 1/4 3-10 change.

Record by Chas Armstrong - 5-1900 Ret N&L 2639.34.

W Frazed did not check east

stone found 5.45 west and 2.65 north of J Kerr C/M.

stone now 1.54' north of direct line

3.08' west of Midway

Meas east 2633.24

Meas west 2627.08 East 1/2 1313.36 West 1/2 1313.72

1/16 corner with .1' of direct line 1/4 corner and S W 3.

Meas north 2646.1 to Center 3 now 1" rod

4.53 dist East of J Kerr C/M at Center 3

Meas south to RR spike as prior corner to date 2632.25

P.D. Survey (1916) Stone found meas. East 2652.9
West 2616.6

Govt Notes M. Karrick 1854
40.00 Set temp. 45-link post
West on true line between sections 34 & 10
V 9° 21'
Set 1/4 section post
Jack 6 N 84 E 185
Bur Oak 10 S 60 W 80