1 5/24/84 set C.I.M. orc ½" x 15" rod #840408 ①

¼ corner. North ¼ 4 Aronoco 10 8-14.

6-1891 Thos Fraser. unrec 84 p95 book 7 [illegible]

corner not found. run north line sec 4 79.15

set corner in order to set center 4. likely M & L 39.575

- meas south. record 40.44 - actual 40.63 3/4.

no dec 4 corner - typical T Fraser corner.

P.D. Survey 1916 stake found meas. East 2627.1

South 2673.8

6-6-83, N ¼ 4 : Dug but found nothing - See Excavation Report

Digging to cover a point midway between the section corner and Thomas Fraser's measure from the fence at the 1/16th (stakehole #6) South and also the E-W ¼ line

Sec. 4 (which comes 7½' North of line from NW4 to NE4 and appx 6' North of line from S. 32-33 to S¼ 33)
Also covered line from S¼ Cor 4 over ~~area~~ stake hole 7d at the 1/16 N of the Center 4 which came appx 5' West of the midway point. Fence running West is 8½' North of line from NW 4 to NE4. Dug from a point 5' North of point midway and on line between NW4 and NE4 as follows:



could not dig farther East became ditch there at end of huge culvert. Area filled with rock fill from road construction. Dug 3 to 4' deep. Found nothing

#840408 (2)

North 1/4 Cor. 4, Oronoco, 108-14

5-24-84, N. 1/4 Cor 4: Set a C.I.M. over a 1/2" x 15" re-rod on the corner midway the CIM @ the North Sec. Cor. 4-5 and CIM @ N. Sec Cr. 3-4, and on line between pipe @ S. Sec. Cor 32-33 and the pipe @ the S 1/4 33. Put survey marker sign and post 1.0 E'ly. The corner came 4' S'ly of the hole dug in 1983 and on North side of a large culvert (N'ly of two) and in E'ly road ditch and in line fence West on W. side of road.

RP's: Spike and CSD in E. side 13" Burr Oak N13°E 23.55

.:. in top of NE'ly end large culvert (S'ly of two) S38°E 26.63