/ 8-30-72 dug up entire road no corner.
4-28-78 CTM

#1
#841304

1/4 Corner 13-24 Aroroco 108-14.

5-1877 Hunter P308 no 302 S24&25 Rowley, Webster Stark & others

found stone set in center road set by Henry Webster and Charley Brooker were original corner stood

-16 east set temp stake for line to set center NE 1/4 24.
M & L 19.93 (1315.58'

1307.46

-16 center NE 1/4 24. set marked stake. M & L 19.81
1307.46' on N-S 1/16 line.

- meas south. 39.39½. (2600.07

T. H. Bk 5 p.1 Sec. 24 5-1877
set stone 6x10x18 at 1/16 Cor. South

1972 (over

8-30-1972. found true stone at 1/4 24-25 and reset C/M over stone - found 1877 stone set as 1/16 corner 1310.36 north of 1/4 24-25 - set 1/2" rod as center 24 by line over 2 stones found and doubling distance.
- ran electronic traverse north around hilly offset road to nail in center road in line fence east and west in area of 1/4 13-24. road here on sharp slope down from some 600' south with road cut. dug entire road in area of corner with backhoe. road eroded to clay but dug carefully. found track down to clay.
- set 1/20 nail 4' east of west edge road in line fence at record. 2600.3± also 1/20 nail on hill south on traverse POT 2169.25 - this nail 4' E of W edge road. at farm entry east - eye line nail and S edge closest elm tree to N.E. edge Gas tank. Must Meas E.

¼ Corner 13-24 Oconoco 108-14 *2
#841304

6-1-76 Dug with backhoe to cover T.H. measure from E. Dug from W. edge previous diggings to 6' E of 120d. Found nothing. Road cut at 4' depth



4-28-78 Reset a C.I.M. on a 15" "T" bar in line with the E-W fences and on the N-S ¼-line of Section 24. This made the distances East & South about 3 to 4' short of T. Hunter the same as the other ½ miles in this survey. Dug extensively here in 1972 & found the road very cut at this time.

R.P.'s Co. Surv. Disc in pp# 35047 W. 85.85
Co. Surv. Disc in 20" Maple N.E. 46.93
Corner falls 5' E of ℄ of N-S Twp road and
in line fences E and W.
Cor. W.-S. m. Hammock 1854
40.00 Set temp. 1/4 steel post
West on true line between sects
13 & 24 V 9°43'
40.00 Set 1/4 steel post in ground
with hammock & bits, chained stakes,
Osage Orange posts N 2 E 5.00