6-26-1964 set CIM ones each weight. (1)
#842009

¼ corner center 20 Aronoco 108-14.
9-1913 Ch Larson P 196 B L 20. C Clasen.
set iron stake each line 3' dup at inters lines.

1913. 4 surveyors. big survey. P 219. bottom page.
run E-W ¼ line set stake midway & line 2638.7 to
told point and stake at 3000 to hold line. Late run
N-S ¼ line and intersected point which came slightly
east of first point - each 2638.25 west 2638.95
doesn't quite jibe but shows east half ½' shorter than W ½.

Co H D 1968 B 326. meas east 2633.08 from present
CIM. meas 22' south to CIM from Stat 236+18.11
22.06'

center 20 set 1"x 3' pipe by inters lines on survey. J Kerr.

6-1964 J Kerr set C/M ones sash weight to preserve corner. Origin of pipe doubtful as iron set on any survey of record as it came in south ditch of road which is new grade and deep.

corner lay in power pole line on W side highway (now gone)

Highway controlled access sign. SSW 10.0.

Disc power pole. SSE 37.2.

corner lies in shallow pit in south ditch E-W black top road. about 25' south center line road.

4-21-1975 Dug & found C. Larson iron rod (1.7' deep) 0.4' W. & 1.7' So. of Tobar stone mon.

RR's to MA Tool
C L ... Blk.

(2)

¼ Corner Center 20 Oronoco 108-14
#842009

9-8-1977 Mn/DoT RP's to CIM

Corner 70' West of ℄ SBL T.H. 52
and 24' South of ℄ C.S.A.H. 12

CN&D up 1.0 on NW side Corner fe. post ~~SW 10.99~~ gone 6-3-85

CN&D up 1.0 on N. side Fence post
(West of Cor. fe. post) ~~SW 27.98~~ 28.08 6-3-85 post in bad shape

CN&D in Brace post (up 1.0 on NW side)
South of Cor. fe. post ~~SW 16.93~~ gone 6-3-85

6-3-85 Fd CIM OK Will shot from King.

CSD West side tele post stub with box SSE 34.44

