X Set CIM 6-24-81 #842104 (1)

1/4 corner. 21-28. Oronoco 108-14.
3-1896. Ft Fraser. 1592 no 538. W½ S28-E½ S27.
S Hall, W. Froman
found corner fence post in center of mound
with mound and pits plain - drove marked stake in mound
post in line fence east and west by post
- east located corners for property boundary.
at 14.43 3/4 (952.55' ) then 5.47 1/4 (361.2 to
-16 corner at M & L. 19.90 1/2. to NE cor 28
where stake found, replaced with 2 stones. P555.

(over)

10-1969 McGhee city dump survey. Run & meas line from
1/4 22-27 west over C/M at north 27-28 on 35' offset south.
set prop cor at 2018.33 a pipe then 585.77 to C/M N 27-28
- found old post stub as prop corner at 1672.8 R 1674.93
Cont line & meas west to N 1/4 28 dug extensively for old
post remains found nothing set 5/8" x 2' rod by record
on line NE 28 over post at prop cor. 1672.8. set rod on
line at 951.6 R 952.5 1/2 mile 2624.4 R 2627.5
- rod lies 2' south of E-W fence. 5.1' NE to cor post fence N.
Knob cut in brace north of rod. No other R.P.'s no C/M
- prop cor east stones N-E-S of post, rod on west side, comes
in line fence south about 1.9' N ± present corner post.
- an angle of 7' at N 27-28 7' 7' N
- an angle of 90° 14' at 1/16 letter N 1/4 28 and NE 28 south to east

Oronoco 1/4 corner 21-28 #842104 (2)
Geo'l Notes M. Kovick 1954
40.00 set iron pipe section post
West on true line between steel & 21-28
40.00 set 1/4 section post in mound with charcoal, pits, chunks and Orange Orange Stakes N. 8° 55' W. 5.44

6-24-81, 1/4 Cor 21-28: Dug for W. Fraser stake and found ± 4" of stake + 6" of mark down into clay! Set CIM over 5/8" iron. Comm 1½' South of E-W fence and 2' West of fence North. Nailed sign on brace 1.5 North of CIM.

RP's Spike in Cor. Post NE 2.28
Spike in Brace Post NW 5.16

CIM approx 3.5' East and .5 North of Mc+B iron rod which we removed.