6-26-1964. set C/M deep in cultivated field. (1)

1/4 corner 20-21 Oronoco 108-14.

#842106

7-1912 Ch Larson P196 B 2 20 I placed.

set stake N & L 40.00 to set center 20 only.

1913 Williams & others P 219 just below middle page.

corner gone. set corner. N & L 2615.6 or 1/3 distance

1/4 16-17 and 2 E corner 20.

- Meas west to center 20 set inter lines 2638.95.

- corner came. 24.4 south of E-W road fence on S side of road and 15' west of fence N & S.

—over.

4-1960 JKerr B 78 P75.
set iron as corner. on running line 1/4 16-17 to SE20.
~~total~~ 7841.5 1/3 2613.83. R 1913 2615.6.

6-1964. set C/M over iron well below plow as corner corner in open cultivated field south of road.
- fence running north on N side road lines with corner.
- no N-S fence on south side road. Common land.
- NE corner house. SW 10 6.1.
- Steel fence corner. on N side road RW N 85.55.
- Sp tele pole NW 42.35.
- aprox ℄ E-W road. N 52.0.

Meas east Co H.D. B 326 1968 5261.33 on meas on ℄ road and going 90° at both ends. - Meas west to center 20 on ℄ road Meas. 2633.08. same 90° to iron Sta 209+85.03 51.91 south to Cor

1/4 Corner 20-21 Oronoco 108-14 (2)
842106

Cedric Schultz of Tom Taylor Co reported on 5-28-1974 that he dug up a large concrete (13" dia) monument in the center of the road 54.5' North of the CIM set by Ken. Top of concrete down 1.7 in the road. Did not use this monument as original undisturbed.

SEE Blue Book For Analysis.

Govt Notes M. Hancock 1854
40.00 Set 1/4 section post in mound with French. pitts, charred stake, and Osage Orange stakes N. E. & S. W.