4-27-1967 set CIM oner. iron rod #842305 ①
section corner 22-23-26-27. Oronoco 108-14
6-1881 Hunter surv. P123 No 371. old field book. J. D Blake.
section sub-divided - shows north line S26 at 39.66
M&L which indicates N¼ corner set M&L to set center.
may have been measured only. 2617.6 M&L record.
See Field BK 14 p.79 12-1886 T.H. — found stake

5-1902 H Fraser P186 S26. H Frederick, W Koewing.
refered to Hunters unrecorded survey as page 123
of field book for J D Blake. — Meas copied from Notes

1941 J Kerr B23A power dam survey.
found very rotted but definate stake 1.5' south of
old corner post: drove ½" x 3' pipe thru stake over-

set small stones about pipe.
- Meas west 2636.18. To N 1/4 27. then 2606.05 west to NW cor 27.
- Ran line south to SE 27. set E 1/4 27 M&L.

see 1/4 26-27.

8-27-41 J Kerr B25 P70 Kalbe.
Meas north line 26 - 4300 feet by Triangulation. set point close to east end of line. this line a nightmare. 5221' ±

4-1967. found pipe by streaching old fence pulled out of woode SW of corner. easily found pipe with needle. 1981
set C/M over pipe.
- pepsi cap in new 6" black gas post 3' S of E ~~27.8~~ 27.89
- 1/2 harrow tooth driven 1' up E side 14" oak SSW ~~+8.6~~ 18.52
- " " " " 2' up N side 30" elm WSW 22.68

corner. 3' N of E-W fence - 1' W of fence running south.
OK — box elder
P.D. survey shows Iron Pin as Corner

Ornamental section corner 22-23-26-27 (2)
Govt Mon. M. Kanick 1854 #842305
80.00 Std post for corner to section
erected mound w. 4 trench, pits 22-23-26-27
charcoal stake, and Osage Orange Scribs
at each angle

7-23-81 found CIM OK with piece of concrete block on So. side. Set survey marker sign and post 2.45 So on the N. side E-W Fence. Checked and corrected ties.