K

#842904 (1)

1/4 corner 29-32 Oronoco 108-14
5-1873 Hunter P224 No 227 S32. R Williams, A Hannon.
found long granite stone in center road.
- meas east 39.80 (2626.8' to stone corner.
- meas west 666 2/3 (440' then 13.33 1/3 (880'
then 19.75 (1303.5 to boulder stone set as corner by Brockway.
total meas west. 2623.5 M&L Rec 2625.15
corner as found 1.65 east of M&L. 3.3' diffm ½ miles
- 16 south set sandstone 6x10 x 18 M&L 19.95 1/2 (1317.03'
- set stake not marked 9.91 (654.06' north center 32.

9-1966 J Kerr. run & meas line NE 32 to NW 32 (cross in bridge. total mile 5257.3 set ½"x 3' rod on true line
- 2627.7 west, 2629.6 east as set

- over -

dug 12' X 20' to clear soil - soil sandy rocky loam hard to dig or tell where anything ever laid. (See bottom Card 2)
- run & meas line making 1/16 stone south found under fence east of corner post and stone found (several found) at center, used small rod by stone as zero. line came 1315.4 to stone 1/16 corner on pushing line north the direct line between section corners would be 1316.65 to stone. if stone set properly at center 32 and N 1/4 M & L. little rod would go .65' south and 1.0' west.
- rod placed as N 1/4 32 would go .95' east to be M & L. or 2628.65
Note as records show east 1/2 3.3' longer than west 1/2 and center would come very near corner post if that proportion used. rod should not be set M & L.
RPS. steel angle corner post NE 25.8
Corner lies 10.9' west of fence running north.
" " 25.8' north " " " E & W

7-22-70 Co surv. decided to leave rod as is as corner (see center 32.

#842904 (2)

Card # 2 1/4 29-32 Arroyo 108-14.

7-22-70 Co surv. came to set C1/4 decided first to set center 32. - meas east of center 32 and found 1/16 stone at 1317.9 R 1318.18 from line already used north set 1"4x4' pipe on center 32 on orig line & rake touch set as 00 in 7-1966 - set pipe 1.1' south of rake touch making 1316.5 from 1/16 stone south. 1316.05 north to direct E-W section line. Orig granite stone may have been slightly north of direct line

meas east 2629.6 R 2626.8 4-26-72 found stone 2' west at NE 32.
west 2627.7 R 2623.5
south 1316.05 and then 1316.5 R 1317.03 M+L.

Over 4-1972

4-26-1972. found recorded stones at 28-29-32-33.
2.0' west and .3' south of C/M as set.
so now rod at 1/4 29 32 would be almost exact M & L.
2627.7 I could could be set .15' south to be true line.
Note - as quoted in Book 32 the 1/2" x 3' rod now in place
as 1/4 29-32 was on projected line from Center as set
and 1/16 stone north. and on direct line between Cross
in Cove stub Bridge west and C/M @ NE 32 (which now
is .3 S and 2.0' west due to finding orig stones) still
would not move rod any further south. Set C/M on rod 4.155

7-1-1902. Robt Fraser old fieldbook #10 p 50-51
at "B" could find nothing although we measured. brick from
A and from 1" (1/16 N of cable) the distances as given by Hunter.
apparently set nothing. Hunters Meas A to B, was 4 to cable All 4L. 2.64E
of 1. "to 2.

Card # 2. 1/4-Corner 29 32 Cronco 108-14 (2)

4-20-73 found 1/2" x 30" iron set 7-1966. #842904 road to be graded from almost nothing - corner rod removed and reference rod set, the 1/2" x 30" rod formerly corner - ~~set on transit line to be plotted on PP in total~~ 1/2 ~~mile with some 300 ft east of 1/4 fence corner~~ No longer good

RP. 1/2" x 30" rod 10' E & N 70' under fence down 10" - used dozer at 1/16 east and 440' from 1/4 29-32 also at 1/4 29-32 found Kota trace at 1/16 or 440' and stone hole at 1/4 29-32 about .55 N and .25 E of rod at 1/4 29-32. No decision as to that corner change. "Decision made To accept ~~spot~~ where stone was or 0.55' N & 0.25' east of Rod location which we moved." (April 11, 1975.) over

Set C.I.M. over 5/8 x 9" rod. April 11, 1975 R.B.

R.P.'s: Punch hole W. end 18" C.M.P. 3' W of N 28.02'
Punch hole E. end 18" C.M.P. NE 37.78'
1/2" rod under fence NNE 69.37'
Corner falls 2 1/2' N & E-W Imp. road
and 10 1/2' west of fence line running north.

Gov't Meters N.E. Cor. 185 ±
40.00 Set temp 1/4 section post
West on fence line between sects 29.32
40.00 Set 1/4 section post in mound of stone
with bronze pipe, chiseled stone,
& Osage Orange scribed N. E. S. W.

1/4 Cor 29-32 108-14 Oronoco #842904 (4)

6-4-98

Fd CIM with Head Missing 15" deep in Crushed rock
Twp Rd 2' So of ℄ & 11' west of ℄ c No.

"842904" H

1/4 Cor 29-32 108-14 oronoco Fd CIM with Head Missing 15" deep in Crushed rock Tw Rd 2' So. of ℄ & 11' west of Fe No.