6-8-77 ½" rod over recorded stone
11-8-77 Set CIP over ½" rod as corner

#843204
①

X

¼ Corner south ¼ 32 Aronaco 108-14.
north ¼ 5 Cascade 107-14.

5-1874 Hunter P249 No 250 S 32. A Monilon, Peters
Corner plowed out in building road, but Mr. M Bereke.
owns his fence south was 1 foot east & due south
on his own land and started 2 rods from corner when
it was standing, set stone 8 x 9 x 22. a boulder sunk well down.
-east set property corner stakes (prop. in Sec 32) on line at 4.04½ chs
16.00 to 1/16 M & L, thes 1002¼ thes 1002¼ to Sec Cor.

7-1917 J Kerr P270B S 5 & 6 Chas Young.
found stone p. 249.
-Meas east 2642.3 with point M & L. -over.

÷ Meas west to stone. 26 39.5
-16 south set stake at 1294.75 - then 1320 to center 5.
-16 center NE 1/4 5 set stake M&L 1319.5 on E-W 1/16 line
-16 center NW 1/4 3 " " " 1318.8 " " "

6-7-77 Found recorded boulder 5' deep. Set 1¼"x15" pipe on the E side and a ½"x12" rod on the W side
6-8-77 Set a ½"x2' rod at the surface of the road. Corner ½' So ℄.

RP.S CSD N side pp # 39577 SW 97.89
Punch mark in lug at top W. end CMP in driveway So. SE 43.13
Punch mark in lug a top W end CMP in driveway N. NE 39.98

#843204

(2)

S¼ 32 108-14 Oronoco
N¼ 5 107-14 Cascade

5-13-98

Set Ref pipe 52½' south of CIM Before Cold Recycling CR#14

↑ @ Ref Pipe

⊀ R+ PK in PP #24127 (1st pole east so side)

⊀ = 275°18'09"

Hor = 52.495

✓S¼ 32 108-14 Oronoco "843204" D

N¼ S 107-14 Cascade 5-13-98 MW EA

Set Ref pipe 52½' South of CIM

Re For Cold Recycling CR #14

T@ Ref Pipe

RT P.K in PP # 24127 (1st pole east so. of TO N¼ S

275° 21' 14" dh 00 277° 15' 30" dh 00

0° 03' 10" dh 03 1° 57' 16" dh 03 = 275° 18' 09"

275° 18' 04" 275° 18' 14"

To N¼ S (CIM) (falls ± 1' so. ℄ CR # 14

VA 88° 26' 16" dV 09

Slope 52.515 Hor 52.495

Tie 53.5' North to ℄ CR # 14

8-18-98

✓ N 1/4 COR 5 CASCADE 107-14

S 1/4 COR 32 ORONOCO 108-14 "843204" e

SET PK NAIL @ SURFACE 1½' S ℄ CR # 14

57' E ℄ FIELD DRIVE SOUTH

IN LINE OF FENCE SOUTH

"843204" S 1/4 COR 32 108-14 5-25-99
FOUND PK NAIL @ SURFACE SET BY SURVEY
CREW. SET 1" SS PIPE W/CAP @ SURFACE.
CORNER FALLS 1' S OF ℄ CR 14, 44 1/2'
W OF ℄ OF EAST DRIVEWAY OF TWO SOUTH,
55 1/2' E OF ℄ W DRIVEWAY OF TWO SOUTH &
IN LINE OF FENCE SOUTH.