X 6-13-1980 set ½ pipe over stone corner fd 4" deep
#843505 (1)

section corner south 34-35 Aronoco 108-14
north 2-3 Cascade 107-14

2-1889 Hunter P 427 no 415 L3 J Clasen, C Oswald.
found stone as corner. on L side of track in line
of fence running south.
- Meas west 39.90 to temp point set where old
corner stood in previous survey. for line south.

6-1900 R Fraser no 582 P 649 middle page.
found stone and stake P 427. in line with fence ~~north~~ South
and wood Abutt
set boulder stones on top.
- Meas east 39.68 (2618.88' to stone set M & L.
4-24-1979 Shot ½" iron which checked OK into a spud
39.3 NW in a power pole - we found no further
R. P.'s at this time.
- over -

10-1913- D Williams P 240 B. J A Clason S. E¼ S 34.
found stone boulder 6 x 6 x 12 with peaked top in south
wheel track in line of fence south.- run line west 2 miles.
- 1/16 west set standstone on line 1318.9. at ⅛ dist.

Corner found and preserved by J Kerr & Co Hwy Dept.
Corner now rod in black top.
1960 RPs Sp PP NW 37.3 Sp cedar tree NW 55.15.
sp guy pole SSW 31.0 " boulder SW 70.6.

1965 RPs 53 16 P3 Elec. tele pole. NE 6 7.04. Hub & E 100
¾" steel rod " power pole. NNW 3 7.31
" brace pole SSW 30.99.
1937 Meas W 2636.9. 1965 2636.75

Power Dam survey (1916) found Stone Meas. North 2628.0
To Stone fd as ¼ Corner 34-35

(2)

Section Corner South 34-35 Oronoco 108-14
North 2-3 Cascade 107-14
#843505

6-13-1980 Dug with backhoe & found stone 6"x8"x18" near location of iron at surface. Dug 4' to clay. Set ½" pipe on stone found. Stone .14 West and .07 North of iron @ surface Iron { 7.45 W / 8.79 N Stone { 7.31 W / 8.72 N

(1991) C.H.D took Reference to Corner. Set 1" Sq. Pipe w/Cap on line to P.P. ± 350' N.N.W. of Corner @ 249.06' before Construction of C.R. #14

6-11-1993 Set 1" Sq. Pipe w/cap as Corner. The Corner falls in E-W ℄ CR #14 & 6' west of Main & 11th Ave NW
C.S.D. in P.P. ▲ 50400 NE 86.71

C.S.D. in P.P. # 52552 SE 60.99