10/31/90 SET C1C/P 2 #843606 (1)

1/4 CORNER 35, 36 Oronoco 108-14

~~35~~ 36- 1854 Michael Karrik

Govt Notes ~~[redacted]~~, Deputy Surveyor

North between sections 35 and 36

Variation 9° 20' East

7.0 chains Enter dry bottom and timber NW

10.0 chains East fork of Zumbro River runs NW 100 links wide

20.00 chains leave bottom NW

40.00 chains Set quarter section post

Bur oak 12" S 82° W 475 lks (313.50')

Bur oak 8" N 61° E 258 lks (170.28')

1969 Mc Ghie & Betts used corner post, set iron rod at center 36

Power Dam Survey 1916 USED FENCE CORNER measured south 2605.6, measured north 2661.0

10/5/90 LOOKED FOR WITNESS TREE 12" BUR OAK SW 82° 313.50' TAKEN BY GOVT, BUT THERE ARE NO TREES IN AREA THAT WERE BIGGER THAN 12" NOW. WE DUG AROUND C.P. TO FENCE 5' W FROM TRAV. PT. ½' EAST OF C.P., 1½' EAST, 2' WEST, 2½' NO ½, 2' SO. 1½' DEEP SCRAPING ABOUT 6" OF CLAY (FD NOTHING) BUT TREE ROOTS, THERE WERE NO MARKS OF OLD POST HOLES SO IT SEEMS THE CURRENT C.P. IS AT SAME LOCATION AS OLD POST. THERE WAS SOME OLD WOVEN WIRE FENCE LYING ON GROUND RUNNING E-W ABOUT 1' NORTH OF C.P.

CONT →

#843606 (2)

1/4 CORNER 35, 36 ORONOCO 108-14

~~Cont~~. 10/31/90 SET RLC/P² 0.28' SOUTH OF TRAV NAIL TO MATCH M.C.'s BCTS 1/4 LINE FROM EAST IN SEC 36. THE COR. IS ½' EAST OF FACE OF CORNER POST TO FENCE WEST & SOUTH RP'S

SPIKE & CSD IN 4" CHERRY NW 14.72'
SPIKE & CSD IN 6" CHERRY ENE 27.61'
CSD IN C.P. NE 0.91'