8-25-1966 set C I M over ½"x 2' rod in stone with half of orig stone on east & west sides below ground.
11-17-81 set C.I.C./P12
¼ Corner North ¼ 4 New Haven 108-15.
11-1937 A Leonard P 413 B top of page #850408
found stone near fence corner.
- used as line with N ¼ S 5 to set NE cor S 5.
No meas to corner west - used meas set by
Fraser in 1889 39.59 chs (~~39~~ 26 12.9 to set NE 5.

---

8-1966 J Kerr for work in S 5.
found limestone base 4"x16" top 2"x 5" 26" long
standing vertical in E-W position or in range line.
- over -

origin unknown -- corner lies just north of fence wire and 2' east of corner post of fence south. - No fence north as Goodhue County corner 10.25 chs west. Record shows iron rod set 943.4' east of N 1/4 5 on line (P 473) of N 1/4 5 To N 1/4 4.

---

11-17-81 Set a C.I.C./P² Midway between No. 4-5 and No. 3-4 and on line between So 32-33 and So 1/4 33 The Corner is 4.61' West and 1.83' South of Kerr's C.I.M. (removed C.I.M. but left 1/2" rod beneath in place). This Corner is 1/2' south of E-W fence and 55 1/2' West of an 18" Elm in fence East.
R.P.
Spike in So. Side R.R. Tie fence Post with Survey Sign.
E - 2.64