SET ½" x 2' ROD 9/15/76 #850509 #1

¼ Corner Center 5 New Haven 108-15

5-1889 Chas Fraser P 428 no 416 & 5 Jewell.
Field BK 6 P. 5-8
found stake used many years, 4' deep accepted as corner.
Of "K" Cen. 5 planted stone to Brick
-16 west set stake M & L 19.91½. (1314.4'
-16 north " " at 20.07½ then 22.08 to N ¼ cor.
Could be 22.16 (11.08 + 11.08)

---

11-1937 A C Leonard P 471 B top page. & 5
11.04 m.f
11.08 BK
found corner stone in center road. 6" deep.

| | | |
|---|---|---|
| Sp F post | NE | 47.2. |
| " " | SE | 37.8 |
| Cor " | W | 33.0 |

- meas north to N ¼ 5 2780.5' - over -

8-1966 J Kerr B 94 P 43 Dr Pearson.
set N 1/4 S by A Leonard notes.
found S 1/4 S Recorded stone - set C/M.
- run N-S 1/4 line set 1/2" rode about 2 1/2' apart on this 1/4 line straddling fence line west.
- found nail in center used by Co Hwy Dept as center road in line fence west.
corner rode as set lie 20.3' east of nail and 5' east of east edge of black top in ditch slope.
- meas north 2782.5 ± fence line west to N 1/4 S

---

8-1934 C.H.D. Book# 82 Page 4 found stone
11-1934 C.H.D. Book# 82 Page 78 - set 3"x 6"x 18" limestone about 1/2' below surface

9-15-76 Corner found.

¼ Corner Center 5 New Haven #2
108-12
#850509

9-15-76 Dug at nail found 2½' W of ℄. Found 4" x 6" x 12" limestone over a piece of boulder and 2" x 15" x 18" limestone side-by-side over a brick over a stake 4' deep in clay. Set brick back over stake and stones found, asphalt chunks, and 2 shot rods over brick. Dug in 

. Corner 2½' W of ℄ and in line with fence W. ℄ Set ½" x 2' rod at surface.

R.P.'s: C.S. Disc in telephone pole WNW 32.88
Punch mark in lug N. end 24" C.M.P. NE 65.19
C.H.D. Disc in pp #35 NE 45.51
C.H.D. Disc in pp #40 SE 111.53

9-20-85, Leonard Prop. Cor. 656.4 East of Center 5: Fd 3/4" iron down 14" in field and 19' North of center of field road. Iron 656.46 elec. east of Center 5.

9-20-85, Leonard Prop. Cr 943.4 East of Center 5: Spiked for iron 287.0 East of iron Fd (above). Fd nothing

(850509) Center 5 108-15
New Haven Twp. 8-25-83
V. Fangman fd 1/2" Iron @ Center
Sec 5. Set 3/4" pipe nzer
over 1/2" Iron. This pipe has
been used many times in
Certificates of Survey filed
in County Surveyors office.