/ 11-3-71 found recorded stone - set iron on N side.

#850704 (1)

1/4 corner 7-18 New Haven 108-15.

7-1893 & Fraser P524 No 489 Sec line 7-18 & P. Gorman.

Corner could not be found, no evidence to relocate it.

- set stone 3 x 8 x 24 on line and 40.04 (2642.64' from SE cor S7.

- 16 west set stone 5 x 5 x 25 on line with stake at 20.02 - 1321.32 then. 19.22 (1268.52' to SW 7.

- also set 1/64 stake M & L 10.01 S 1/4 7 and 1/16 west.

(over

11-3-71 Co surv. Meas from center road 19.75 ± N of CIM at 7-8-17-18 west about 20' North of E-W fence. - had to shift chainage south at about 2000' as brush too thick so chainage not accurate - fence N at 1314. R 1321.32
- found. limestone 3x8x17 at 2642 ± R 3x8x24 2642.64
- set bottom part of steel fence post on N side of stone, rod down.
- set point 8 north for random line west.
- set nail at 1320.75 on random line 1321.32
- set nail at 2586.20 on random on center road 1286.52

11-9-71. found. 18" of 5x5x.25 L stone at 1/16 corner. at 13.56 N and .1 E of 1320.75 nail.
set 1" x 4' thin iron pipe on west side of stone. with glass and multi colored stone on east side of stone.
1/16 corner. 2' W of fence running north - 2' N of fence running east. so corner lies 1320.65 west of '47-18. or .67 short.

Lee W 7-18

1/4 Cor. Sec. 7-18 New Haven Twp.

(2)
#850704

Gov. Notes- Cushing, Dep. Sur. 6-12-1854
East on true line between 7 and 18.
39.20 Set quarter section post.
B r. Oak 5 in. S30E 73 lks.
Dug trench.
79.20 Section corner.