/ ~~2 1/2" x 10" iron to line & meas from~~ last 8/7/69 FND SET BRASS (1)
~~Set CIM .82 E of~~ ~~of~~ ~~on~~ stone. PDU
section corner west 7-18 New Haven 10 8-15
850705
7-1893 Jr Fraser P524 no 489 Sec line 7-18 for
found 3 boulder stones with 2 stakes, P Gorman.
driven in between and old horseshoe beside 1 stake.
anered to be where old corner stake stood.
-16 east. set stone 5x5x25 with stake at
19.22 (1268.52' then 20.02 = 1321.32 to S 1/4 1 set on line
Totals = 2589.84
and perp. distances.
- also set 1/64 stake N&L 10.01 between S 1/4 7 and
abne 7/16 corner.
-over)

this line last is S 88°40'W and running due west from SE cor 4 came 182½ links (120.45' north at SW 4.
- meas for mile gave meas 79.20 (5227.2 actual 79.28 (5232.5

2-1892 Chas Fraser P471 No 452 S18 Pat Kennedy. D Kane could find nothing on north line of section - speaks of spending 4 days on S line S 8 so didn't care to on north line which could mean he wasn't working in S 18 at all, but Kennedy and Kane in or next to S18. ground likely frozen and didn't look.

Cap Maxon Pine Islands found stone
Meas north and south
11-1-71. Meas North from .00 nail at W 1/4 18 (S and line pt W).
- set nail at 2614.3 (no record)
- meas north from above nail - found limestone with cross at very near 1320 (Cap Maxon record) just east of old post on N.W. corner small shed. down 10" set long rod on E side.

Card # 2. West 7-18 New Haven 108-15.

11-3-71 found 1/4 7-18 limestone - offset N 8.0' and (2)
ran random line west - set nail at 1320.75 R 1321.32
and nail in center black top at 2586.2 R 2589.84 #850705
11-9-71 found 18" d record 5x5x25 limestone at 1/16
corner at 1320.65± and 13.56 south of random.
set 1" x 4' thin iron pipe on W side 1/16 stone and 12"± long
Multi colored granite on east side L stone which came
2' N each & 2' west corner post of good fence E & N.
- set W (6-7) 7-18 a 3/4" x 10" runt rod 18.85 and 2.33W of
2586.2 nail or 2588.53 from 1/4 cor. 7-18
or 1267.88 from 1/16 stone. R 2589.84 and 1268.52
this line is using S E 7 and 1/16 stone as 1/4 7-18 could
have been shifted in setting post. stone only. 1 N of direct line.

between center 1/16 stone and C/M at S.E.T.

RP W 7-18 final corner 3/4" x 10" iron.

78.0 E. to pipe cap on N side new 5" cedar corner post

30.1 3' N & E To ·:· in S. end 18" field culv

39.97 NE To " " N " "

Corner about 1' S fence running east and 2' west of Center black top S & R #5

9-7-76 Dug with backhoe at rod previously set from East by line and measure. Found 3 boulders with stake between 5½' deep .01 S and .8± E of rod. Dug stake Set 1¼" pipe on S. side of stake. Set CIM ours '76.

W. Sec. Cor 7-18 New Haven 108-15 #3
#850704

9-7-76 Set CIM over 3/4" x 10" rod over pipe as corner. Corner in line of fence E and in ℄ N-S road.
R.P.'s Punch hole top S end CMP to field drive E E 29.30
Punch hole top N end CMP to field drive E N 39.33

Gov. Notes- Ball, Dep. Sur. Oct. 1853
North between 13 and 18.
80.00 Set corner post.
Blk. Oak 4 in. S28E 57 lks.
Br. Oak 5 in. N17E 89 lks.
Built mound of earth and sod andpit 8 lks. south.

7-16-85, West 7-18: This corner may be destroyed by road construction. Took transit tie.

Drove 5/8" re-rod (bent 12") in center of field road running East, 174.53 ENE of corner at top of knoll.

T @ re-rod x Rt W 7-18 to W'ly pde of pair of poles in N-S transmission line 1/4 mile ± east of county line = 163°13'50"

8/7/89 C.H.D. SET 5/8" BRASS PLUG 0.8' WEST OF ℄ C.R. #5 RP.
20.0' NORTH TO ℄ OF FIELD DRIVE