/ 10-6-71 set 3/4" x 30" iron bolt as corner by intre
7-7-72 set C/M over 1/2" x 2' rod) of section, 4 lines.

section corner 9-10-15-16 New Haven 108-75 (1)

12-18 94 Sr Fraser P 556 No 513 S 10, 11, 14, 15
Alker, Campbell, Ackerman Shanks and others.

#851005

Corner claimed gone for many years. No evidence
or knowledge of any kind for corner.

- Meas bare from NE corner 15 to N 1/4 16. short
221 lks. set stake at. 39.27 1/3 R 40.00 from west
then 39.25 5/6. (2591.06' R 39.95 for 2-1/2 miles east. (1 mile)
west 39.27 1/3 (2592.04' to 1/4 9-16.
- set boulder stone as corner, took B. tree
12" S oak N 70 1/2° E 17 links (11.22)

over

To set N & S — meas from 3-4-9-10 to 1/4 16-15
R 40.00 overrun 33 ehs or 40.11 2647.26

10-6-71 Co surv. ran & meas line from east (SE 10
meas from SW 9 east.
- proj line from 3-4-9-10 over 1/4 and 1/16 corners south.
set 5/8 □ head 30" bolt at inters of lines. 16' east of
line from north to put on exact record meas. and
exact line from east.
- meas east to 1/4 10-15 C/M monestone. 2591.06 (record).
- meas west to SW cor 9. stone found. 5245.06. R 5245.24
- Corner 5' S of center road and 5' W of fence line south.
35.0 5' E of S. to hard nail thru pepsi cap top RR tie Cor P.
143.22 WNW to center numberplate of PP # 23781.
No 6 Meas E showed be. 2591.06 M&L. actual E 2591.06 then 2587.51

#851005 (2)

Se. Corner 9-10-15-16 New haven Twp.

Gov. Notes- John Cushing, Dept. Sur. Aug. 10, 1854
80.00 Set corner post of secs. 9-10-15-16
rasied mound and trench as per instructions
and drove charred stake.